Chest freezer ULT C400



- Low cost of ownership
- Limited maintenance and on-site service
- Easily installable & movable

- Eco-friendly, HCFC-free Nature R refrigerant
- Efficient cyclopentane insulation
- ISO 9001, 14001 & 18001 OHSAS Certified

Specifications Technical Gross volume 383 litres Net volume 368 litres -60°C to -86°C Temp. range Temp. probes 1/PT 1000 Embraco Compressor Refrigerant Nature R Noise level 55 dB 8,10 kWh Power consumption 24/h Power consumption 2.957 kWh/year 220V-240V Voltage Frequency 50 Hz Features Audible & visual alarm YES 4 Castors YES Integrated lock Inner lids 4 Defrost Manual Battery Backup 50h USB NO Data connection NO Digital controller with display XR30CX NO Data logging YES High/Low temperature alarm Porthole for external probe & CO2 backup Ø12 mm

Prepared for external logging equi	ipment YES
Contact for remote alarm	YES
Material Inner Outer	Precoated white steel Galvanized pre-coated steel

Dimensions	
Height	850 mm
Height w. castors	890 mm
Width	1560 mm
Depth	695 mm
Net weight	88 kg

Internal dimensions	
Height	635/385 mm
Width	1190/210 mm
Depth	440 mm
Insulation	80 mm
Insulation type	PUR
Internal humidity	<5 %



Storage capacity						
Box height	No. of boxes	No. of racks	Total no. of boxes	Product no.		
50 mm	6 11	3 24	18 264 = 282	N311200 N311220		
75 mm	4 8	3 24	12 192 = 204	N311300 N311320		
100 mm	3 5	3 24	9 120 = 129	N311400 N311420		



Wolf Laboratories Limited

www.wolflabs.co.uk

Tel: 01759 301142

Fax:01759 301143

sales@wolflabs.co.uk







Use the above details to contact us if this literature doesn't answer all your questions.

Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.





