



Model:
B-510LD2

Typology:
ROUTINE MICROSCOPE

Description:

*Laboratory microscope for routine and research applications.
Dye-cast frame, with high stability and ergonomy, for transmitted light
and fluorescence reflected light observation.*

Illumination	<p>Transmitted light: Light source: X-LED³; light intensity control using a knob on left side of the frame. LED power: 3.6 W, comparable to a 50 W halogen bulb. Color temperature: 6,300 K.</p> <p>Epi-fluorescence: High-efficiency white LED, light intensity control using a knob on left side of the frame. LED power: 3.6 W. Color temperature: 4,200 K.</p> <p>LED lifetime: > 65,000 hours. Power supply: Input 110/240 Vac, 50/60 Hz; Output 6 Vdc 2.5 A. Max. required power: 6 W.</p> <p>Köhler illumination system with Field Diaphragm.</p>
Observation Modes	Brightfield, Fluorescence.
Fluorochromes	<p>3 positions slider, with 2 included filtersets: Fluorescence B: EX 460-490, DM 505, EM 515LP: Acridine Yellow, Acridine Orange, Auramine, DiO, DTAF, FITC, GFP, YFP, etc. Fluorescence G: EX 510-550, DM 570, EM 590LP: DiL; Blu Evans, Feulgen, Rhodamine, Texas Red, TRITC, PI, etc.</p>
Focusing	<p>Coaxial coarse and fine focusing mechanism (graduated, 0.002 mm) with upper stop, to prevent the contact between objective and specimen. Flat fine focusing knob on the right side. Adjustable tension of coarse focusing knob.</p>
Stage	<p>Double layer with mechanical sliding stage, size 233x147 mm, X-Y movement range 78x54 mm. Belt-drive in X direction. Vernier scale on two axes, accuracy 0.1 mm.</p>
Nosepiece	Quintuple revolving nosepiece, rotation on ball bearings.
Head	<p>Trinocular observation head, inclined 30° and rotatable 360° Diopter adjustment on left eyepiece (+/- 5 diopter adjustment). Interpupillary adjustment 50 - 75 mm. 3 positions photo port: 0/100, 50/50, 100/0 ratios.</p>
Eyepieces	Plan Extra Wide Field, PL 10x/22, High Eyepoint.
Objectives	<p>Infinity corrected optical system IOS. - IOS W-PLAN 4x/0.10, W.D. 17.3 mm - IOS W-PLAN 10x/0.25, W.D. 10 mm - IOS W-PLAN 40x/0.65, W.D. 0.54 mm - IOS W-PLAN 100x/1.25, W.D. 0.13 mm (oil immersion) All objectives have anti-fungus treatment.</p>
Condenser	Swing-out type condenser, sliding-in, N.A. 0.2/0.9, with centering system.
Dimensions	<p>HEIGHT: 490 mm WIDTH: 270 mm DEPTH: 470 mm WEIGHT: 10.8 kg</p>
Accessories	Instruction manual and dust cover included.



Wolflabs

Wolf Laboratories Limited

www.wolflabs.co.uk

Tel: 01759 301142

Fax: 01759 301143

sales@wolflabs.co.uk



Use the above details to contact us if this literature doesn't answer all your questions.

Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

