



Monocular microscope, 600x, achromatic objectives

Observation Method -	Brightfield	Yes
Transmitted Light	Simple polarized light	As optional
Main Body	Туре	Upright
	Construction material	Aluminum die-cast
	Trasportation handle	Yes
Head	Туре	Monocular
	Inclination	45°
	360° rotating	Yes
	Fixing screw for eyepieces	Yes
	Tube inner diameter (mm)	23
Eyepieces	Field number (mm)	18
	Magnification	10x
	Pointer	As optional
	Micrometric scale	As optional
Nosepiece	Positions	Quadruple
	Reversed	Yes
	Bi-directional	Yes
	Rotation on ball bearings	Yes
	Objective thread	RMS
Objectives	Optical system	160
	Anti-fungus treatment	Yes
	Parfocal distance (mm)	35
	Standard magnifications	40x-600x
	Туре	Achromatic
		4x/0.10, W.D. 10.6 mm
		10x/0.25, W.D. 7.0 mm
		40x/0.65, W.D. 0.5 mm
		60x/0.85, W.D. 0.13 mm
Stage	Туре	Double layer
	Dimensions (mm)	125x125
	Moving mechanism	Rack and pinion
	Moving range (mm)	62x24
	Material	Anti-scratch painting
	Specimen holder	Yes
	Slide number	1

Vernier scale accuracy (mm)	0.1
-----------------------------	-----

X-Y Vernier scale

Condenser - Single	Туре	Abbe
Position	Numerical aperture (N.A.)	1.25
	Diaphragms	Iris
	Focusable	By rotation

Yes

Focusing System	Туре	Coaxial coarse & fine
	Coarse total travel (mm)	23
	Fine total travel (per single rotation) (mm)	1.2
	Fine graduations	100
	Fine resolution (µm)	12
	Upper stop to prevent contact	Yes

Transmitted	Туре	LED
Illumination	Light source power (W)	1
	Brightness control	Manual
	Lifetime (hours)	> 65,000
	Temperature (K)	6,300
	Max. required power (W)	1.5
Power Supply for	Туре	External
Transmitted	Microscope connector	Jack, 2.1 mm
Illumination	Power plug type	Multi-plug (EU, UK, US)
	Input voltage	100/240 Vac, 50/60 Hz
	Output voltage	5 Vdc 500 mA
	Rechargeable batteries	Yes
	Battery type	Ni-MH (3x, AAA size)
	Working time of batteries (hours)	4
	Charging time of batteries (hours)	8
Accessories Included	Dust cover	Yes
	User Manual	Digital version (downloadable)
Product Dimensions	Height (mm)	330
	Width (mm)	135
	Depth (mm)	235
Product Weight	(kg)	2.7



Wolf Laboratories Limited

www.wolflabs.co.uk

Tel: 01759 301142

Fax:01759 301143

sales@wolflabs.co.uk



Use the above details to contact us if this literature doesn't answer all your questions.

Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.





