



Stereomicroscope, with pillar stand, 20x-40x, with rechargeable battery

Observation Method - Transmitted Light	Brightfield	Yes
Observation Method - Incident Light	Brightfield	Yes
Head	Туре	Binocular
	Construction material	Aluminum & Plastic molds / Aluminum gears
	Inclination	45°
	Interpupillary distance (mm)	53-75
	Dioptric adjustment	On both tubes
	Fixing screw for eyepieces	Yes
	Tube inner diameter (mm)	30.5
Eyepieces	Field number (mm)	20
	Magnification	10x
	Micrometric scale	As optional
	Diameter of micrometer glass (mm)	20
	Rubber cup	Yes
Objective	Optical system	Greenough
	Anti-fungus treatment	Yes
	Objective Type	Achromatic
	Working distance (mm)	57
	Standard magnifications	20x, 40x (rotating turret)
Focusing System	Туре	Coarse
	Coarse total travel (mm)	37
	Adjustable tension	Yes
Stand	Туре	Pillar
	Pillar diameter (mm)	14
Stage	Frosted diffusion plate for transmitted ill.	Yes, diameter 60 mm
	Black/white contrast plate for incident ill.	Yes, diameter 60 mm
	Specimen clips	Yes
	L	
Transmitted	Туре	LED
Illumination	Light source power (W)	1
	Brightness control	Manual
	Lifetime (hours)	> 65,000
	Temperature (K)	6,300
	Max. required power (W)	1.5

Incident Illumination Type LED Light source power (W) 1 Brightness control Manual Lifetime (hours) > 65,000 Temperature (K) 6,300 Max. required power (W) 1.5 Power Supply for Illumination Type External Microscope connector Jack, 2.1 mm Power plug type Input voltage 100/240 Vac, 50/60 Hz Output voltage 5 Vdc 500 mA LED Yes
Brightness control Manual Lifetime (hours) > 65,000 Temperature (K) 6,300 Max. required power (W) 1.5 Power Supply for Illumination Type External Microscope connector Jack, 2.1 mm Power plug type Multi-plug (EU, UK, US) Input voltage 100/240 Vac, 50/60 Hz Output voltage 5 Vdc 500 mA LED indicator Yes
Lifetime (hours) > 65,000 Temperature (K) 6,300 Max. required power (W) 1.5 Power Supply for Illumination Type External Microscope connector Jack, 2.1 mm Power plug type Power plug type Multi-plug (EU, UK, US) Input voltage 100/240 Vac, 50/60 Hz Output voltage 5 Vdc 500 mA LED indicator Yes
Temperature (K)6,300Max. required power (W)1.5Power Supply for IlluminationType Microscope connectorExternal Jack, 2.1 mmPower plug type Input voltageMulti-plug (EU, UK, US) 100/240 Vac, 50/60 HzOutput voltage LED indicator5 Vdc 500 mA Yes
Max. required power (W)1.5Power Supply for IlluminationTypeExternalMicroscope connectorJack, 2.1 mmPower plug typeMulti-plug (EU, UK, US)Input voltage100/240 Vac, 50/60 HzOutput voltage5 Vdc 500 mALED indicatorYes
Power Supply for IlluminationTypeExternalMicroscope connectorJack, 2.1 mmPower plug typeMulti-plug (EU, UK, US)Input voltage100/240 Vac, 50/60 HzOutput voltage5 Vdc 500 mALED indicatorYes
IlluminationMicroscope connectorJack, 2.1 mmPower plug typeMulti-plug (EU, UK, US)Input voltage100/240 Vac, 50/60 HzOutput voltage5 Vdc 500 mALED indicatorYes
IlluminationMicroscope connectorJack, 2.1 mmPower plug typeMulti-plug (EU, UK, US)Input voltage100/240 Vac, 50/60 HzOutput voltage5 Vdc 500 mALED indicatorYes
Power plug type Multi-plug (EU, UK, US) Input voltage 100/240 Vac, 50/60 Hz Output voltage 5 Vdc 500 mA LED indicator Yes
Input voltage100/240 Vac, 50/60 HzOutput voltage5 Vdc 500 mALED indicatorYes
Output voltage 5 Vdc 500 mA LED indicator Yes
LED indicator Yes
Rechargeable batteries Yes
Battery type Ni-MH (3x, AA size)
Working time of batteries (hours) up to 8
Charging time of batteries (hours) 8
Accessories Included Dust cover Yes
Tension adjustment tool Yes
User Manual Digital version (downloadable)
Additional Information Maximum sample height (mm): 75
Product Dimensions Total height (mm) 288
Base height (mm) 45
Base width (mm) 183
Base depth (mm) 205
Product Weight (kg) 1.8



Wolf Laboratories Limited

www.wolflabs.co.uk

Tel: 01759 301142

Fax:01759 301143

sales@wolflabs.co.uk



Use the above details to contact us if this literature doesn't answer all your questions.

Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.





