/ 2 1 2021



Binocular stereozoom microscope, 7x...45x

| Observation Method - Transmitted Light | Brightfield | Yes |
|---|--|---|
| Observation Method - Incident Light | Brightfield | Yes |
| Head | Туре | Binocular |
| | Construction material | Aluminum & Plastic molds / Aluminum gears |
| | Inclination | 45° |
| | 360° rotating | Yes |
| | Interpupillary distance (mm) | 51-75 |
| | Dioptric adjustment | On both tubes |
| | Head holder internal diameter (mm) | 76 |
| | Tube inner diameter (mm) | 30 |
| | - and minor diameter (min) | |
| Eyepieces | Field number (mm) | 21 |
| | Magnification | 10x |
| | Micrometric scale | As optional |
| | Diameter of micrometer glass (mm) | 23 |
| | High eyepoint (for glass wearers) | Yes |
| | Rubber cup | Yes |
| | Retractable protections | Yes |
| | · | |
| Objective | Optical system | Greenough |
| | Anti-fungus treatment | Yes |
| | Objective Type | Achromatic |
| | Zoom type | Parfocal achromatic |
| | Working distance (mm) | 100 |
| | Standard magnifications | 7x-45x |
| | Zoom ratio | 6.43 |
| | Ohioativa numariaal anautura | 0.02 @ 0.7x |
| | Objective numerical aperture | 0.07 @ 4.5x |
| | Objective resolution | 59 lp/mm @ 0.7x 208 lp/mm @ 4.5x |
| F' 01 | - | |
| Focusing System | Type | Coarse |
| | Coarse total travel (mm) | 110 |
| | Adjustable tension | Yes |
| | Head holder internal diameter (mm) | 76 |
| Ctond | Time | Fixed over |
| Stand | Type | Fixed arm |
| | Handle | Yes |
| Stage | White diffusion plate for transmitted ill | Voc. diameter 100 mm |
| Stage | White diffusion plate for transmitted ill. Black/white contrast plate for incident ill. | Yes, diameter 100 mm As optional |
| | | · |
| | Specimen clips | Yes |
| Transmitted | Type | EcoLED |
| Illumination | Type Prightness central | |
| | Brightness control | Manual |
| | Lifetime (hours) | > 65,000 |
| | Temperature (K) | 6,300 |

| Incident Illumination | Туре | EcoLED |
|-------------------------------|------------------------------------|--------------------------------|
| | Brightness control | Manual |
| | Lifetime (hours) | > 65,000 |
| | Temperature (K) | 6,300 |
| | | |
| Power Supply for Illumination | Туре | External |
| | Microscope connector | Jack, 2.1 mm |
| | Power plug type | Multi-plug (EU, UK, US) |
| | Input voltage | 100/240 Vac, 50/60 Hz |
| | Output voltage | 5 Vdc 500 mA |
| | LED indicator | Yes |
| | Rechargeable batteries | Yes |
| | Battery type | Ni-MH (3x, AA size) |
| | Working time of batteries (hours) | up to 8 |
| | Charging time of batteries (hours) | 8 |
| | | |
| Accessories Included | Dust cover | Yes |
| | User Manual | Digital version (downloadable) |
| | | |
| Additional Information | Maximum sample height (mm): | 100 |
| | | |
| Product Dimensions | Total height (mm) | 365 |
| | Head height (mm) | 230 |
| | Head width (mm) | 140 |
| | Head depth (mm) | 150 |
| | Base height (mm) | 30 |
| | Base width (mm) | 205 |
| | Base depth (mm) | 280 |
| | 1 / | |
| Product Weight | (kg) | 3.5 |
| | 1 | |



Wolf Laboratories Limited

www.wolflabs.co.uk

Tel: 01759 301142

Fax:01759 301143

sales@wolflabs.co.uk







Use the above details to contact us if this literature doesn't answer all your questions.

Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.





