

Trinocular stereozoom microscope, 6.7x...45x, overhanging stand

<b>Observation Method -</b>	Brightfield	Yes
Incident Light	Simple polarized light	As optional
_		
Head	Туре	Trinocular
	Construction material	Plastic mold / Aluminum gears
	Split ratio	Fixed. 70 (eyepiece) / 30 (photo)
	Inclination	45°
	360° rotating	Yes
	Interpupillary distance (mm)	51-75
	Fixing screw for eyepieces	Yes
	Head holder internal diameter (mm)	76
	Tube inner diameter (mm)	30
	Table miles distincted (miles)	
Eyepieces	Field number (mm)	23
	Magnification	10x
	Planar type	Yes
	Micrometric scale	As optional
	Diameter of micrometer glass (mm)	26
	High eyepoint (for glass wearers)	Yes
	Dioptric adjustment	Yes
	Rubber cup	Yes
	Retractable protections	Yes
Objective	Optical system	Greenough
	Anti-fungus treatment	Yes
	Zoom type	Parfocal achromatic
	Working distance (mm)	110
	Standard magnifications	6.7x-45x
	Zoom ratio	6.72
	Za am aliak atana	At 0.67x, 0.8x, 1x, 1.2x, 1.5x, 2x, 2.5x, 3x, 3.5x, 4x,
	Zoom click stops	4.5x
Focusing System	T	0
Focusing System	Type	Coarse
	Coarse total travel (mm)	50
	Adjustable tension	Yes
	Head holder internal diameter (mm)	76
Stand	Туре	Simple overhanging
Otalia	Pillar diameter (mm)	32
	i mai diameter (mm)	JZ
Accessories Included	Dust cover	Yes
	Immersion oil (10ml)	No
	User Manual	Digital version (downloadable)
		g.tai. 70101011 (u0 11111000000)
Additional Information	Maximum complete sight (m)	202 /from hon-h)
	Maximum sample height (mm):	223 (from bench)
Product Dimensions	Total height (mm)	420
	Head height (mm)	240
	Head width (mm)	167
	Head depth (mm)	200
	Base height (mm)	80
	Base width (mm)	230
	Base depth (mm)	230
	Horizontal arm (mm)	430
_		
Product Weight	(kg)	15



## **Wolf Laboratories Limited**

www.wolflabs.co.uk

Tel: 01759 301142

Fax:01759 301143

sales@wolflabs.co.uk







Use the above details to contact us if this literature doesn't answer all your questions.

Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.





