#### B-150POL-B

#### EN

### ΟΡΤΙΚΑ



Model: B-150POL-B

Typology:

#### EDUCATIONAL POLARIZING MICROSCOPE

**Description:** 

Educational microscope for routine applications. Dye-cast frame, with high stability and ergonomy, for transmitted light observation.

Model	<b>B-150POL-B</b> : binocular with rotatable stage; objectives 4x, 10x, 40x.
Illumination	Light source type: white LED; light intensity control using a knob on left side of the frame. LED power: 1W. Color temperature: 6300K LED average lifetime approx.: 50.000h External power supply 100/240Vac, 50/60Hz, output: 5Vdc 500mA. Rotatable swing-out polarizer filter, slide-out analyzer filter.
Observation Modes	Brightfield, polarization
Focusing	Coaxial coarse and fine focusing mechanism (graduated, 0.002mm) with upper stop, to prevent the contact between objective and specimen. Adjustable tension of coarse focusing knob.
Stage	Rotatable stage, diameter 120mm.
Nosepiece	Quadruple revolving nosepiece, rotation on ball bearings.
Head	Binocular observation head, inclined 30° and rotatable 360°. Diopter adjustment on left eyepiece. Interpupillary adjustment 48-75 mm.
Eyepieces	Widefield eyepieces WF10X/18 with field number 18mm.
Objectives	Achromatic objectives with mechanical tube lenght 160 mm, made by following objectives: -) Achromatic DIN 4X, A.N. 0.10, W.D. 18 mm -) Achromatic DIN 10X, A.N. 0.25, W.D. 7 mm -) Achromatic DIN 40X, A.N. 0.65, W.D. 0,53 mm All objectives are treated with an anti-fungus treatment.
Condenser	Abbe condenser, N.A. 1.2 precentered.
Dimensions	HEIGHT: 350 mm   WIDTH: 170 mm   DEPTH: 210 mm   WEIGHT: 4 kg
Accessories	Instruction manual and dust cover included.



### **Wolf Laboratories Limited**

www.wolflabs.co.uk

Tel: 01759 301142

Fax:01759 301143

sales@wolflabs.co.uk



## Use the above details to contact us if this literature doesn't answer all your questions.

# Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.





