v 2.0 2018



Model:

C-P3

Type:

**CAMERA - PRO SERIES** 

Description:

USB 3.0 C-mount Microscope Camera

# **CAMERA SPECIFICATION**

Digital camera resolution	3.1 MP (2048 x 1536)
	` '
Signal output	USB 3.0
Sensor Size	1/2.8"
Sensor technology	CMOS
Sensor type	SONY EXMOR CMOS
Image format	4/3
Pixel size	2.5 x 2.5 μm
Frame rate full resolution	50 fps (2048 x 1536)
Frame rate other resolutions	50 fps (1920 x 1080)
Sensitivity	600 mV at 1/30sec
Dark signal	0.15 mV at 1/30sec
ADC Conversion	8 Bit - 12 Bit
Color Depth	1 Bit; 4 Bit; 8 Bit; 24 Bit
Exposure Time	0.1 msec - 15 sec
Binning	1x1
IR filter	380-650 nm (IR-cut filter)
Camera power	PC USB
C-mount	YES

# **ACCESSORIES**

Calibration Slide	YES
Always Included	1.5 m USB cable

# **ENVIRONMENT SPECIFICATION**

Working temperature	-10 up to +50°C
Storage temperature	-20 up to +60°C
Relative Humidity	30% to 80%
Storage Humidity	10% to 60%
Dimensions	68 x 68 x 46.4 mm
Weight	0.265 Kg

# **SYSTEM REQUIREMENTS**

Operating System	Win XP / Win Vista / Win 7 / Win 8 / Win 10 (32 o 64 bit) OSx (Mac OSx) starting from 10.7.5 Linux
PC Requirements	CPU: Equal to Intel Core2 2.8GHz or higher RAM: 2 GB or more USB port: USB 2.0, at least two ports



# **Wolf Laboratories Limited**

www.wolflabs.co.uk

Tel: 01759 301142

Fax:01759 301143

sales@wolflabs.co.uk







Use the above details to contact us if this literature doesn't answer all your questions.

Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.





