PG14L & PG28L Purge gas generator for FT-IR



Your local gas generation partner

Description

The PG14L and PG28L gas generators from Peak Scientific are suitable for laboratory detectors requiring $\rm CO_2$ free gas such as FT-IR analysis.

Using Pressure Swing Adsorption technology to remove organic contaminants and moisture from air, these generators provide a consistent flow of air to ensure little background noise in laboratory analysis.

Requiring minimal maintenance, the PG14L and PG28L do require an external source of air to operate, Peak Scientific will be able to help with recommending a suitable air source if your laboratory does not have one.

Applications

FT-IR microscopes

Laboratory applications requiring $\mathrm{CO}_{\!_2}$ free air



Key Features

Purge Gas (PG) generators from Peak Scientific offer gas which is free of organic contaminants such as carbon dioxide

Ideal for commercial labs with a high throughput rate of samples

High performance filters and PSA ensure maximum reduction of moisture (< -70°C dew point).

Few moving parts means minimum maintenance requirements and 24/7 performance

Position generator where required, wall mountable for small labs

Most cost effective than any other gas supply as the FT-IR detector needs a constant flow of gas

Completely silent in operation

12 month full comprehensive on-site warranty



| Technical Specifications | PG14L | PG28L |
|-------------------------------|---|---|
| Max Flow Rate | up to 14 L/min | up to 28 L/min |
| Max Pressure | up to 100 psi /6.9 bar | up to 100 psi /6.9 bar |
| Gas Outlets | 1/4" BSP Female | 1/4" BSP Female |
| Dewpoint | -70 °C / -94 °F | -70 °C / -94 °F |
| Particles | < 0.01 µm | < 0.01 µm |
| Min/Max Air Inlet Pressure | 100 psi/6.9 bar - 120 psi/8.3 bar | 100 psi/6.9 bar - 120 psi/8.3 bar |
| Min/Max Air Inlet Temperature | 5-25 °C \ 41-77 °F | 5-25 °C \ 41-77 °F |
| Operating Temperature | 5-25 °C \ 41-77 °F | 5-25 °C \ 41-77 °F |
| Electrical Requirements | Universal 120 / 240VAC / 50 / 60 Hz / 8 A | Universal 120 / 240 VAC / 50 / 60Hz /8 A |
| Generator Dimensions (HxWxD) | 660 x 459 x 162 mm 26.0 x 18.1 x 6.4" | 910 x 459 x 162 mm 35.8 x 18.1 x 6.4'' |
| Generator Weight | 14.4kg / 31.8lbs | 18.6kg / 41.1lbs |

| Ordering Information | | |
|---|---------------------------------|---------|
| Part Number | 45-1010 | 45-1060 |
| Precision air compressor (suitable for PG14L only) | 65-0555 (230v) / 65-1555 (120v) | N/A |
| Annual Service | | |
| FPPM Maintenance Plan | | |
| Complete Maintenance Plan | | |
| Supported Maintenance Plan | | |

[PEAK Protected][™]

Peak Scientific gas generators define the benchmark in reliability, convenience and performance in laboratories around the world, and come backed by a 12 month warranty. Beyond this period however you can ensure that your investment continues to be **[Protected]** by our comprehensive generator care cover.

Our world-class aftercare support packages deliver a program of scheduled preventative maintenance whilst giving you the reassurance of instant access to worldwide technical support and priority on-site response in the untimely event of a breakdown.





Wolf Laboratories Limited

www.wolflabs.co.uk

Tel: 01759 301142

Fax:01759 301143

sales@wolflabs.co.uk



Use the above details to contact us if this literature doesn't answer all your questions.

Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.





