

DISC MILL DM 400



The DM 400 is the new comfort model for fine grinding of medium-hard, hard and brittle materials down to 0.05 mm. This model is based on the well-proven DM 200 but offers improved safety features due to the automatic locking of the collecting vessel and grinding chamber, as well as particularly convenient operation thanks to the motor-driven grinding gap adjustment with digital gap display. The clearly structured display shows all grinding parameters.

Thanks to its robust design, the Disc Mill DM 400 can be used under rough conditions in laboratories and pilot plants, as well as online for the quality control of raw materials. The powerful DM 400 requires only a few minutes to achieve the desired grind size.

APPLICATION EXAMPLES

bauxit, cement clinker, chalk, chamotte, coal, coke, concrete, construction waste, dental ceramics, dried soil samples, drilling cores, electrotechnical porcelain, ferro alloys, glass, granite, gypsum, hydroxyapatite, ores, quartz, sewage sludge, sintered ceramics, slag, soils, steatite, ...

PRODUCT ADVANTAGES

- | excellent crushing performance
- | convenient grinding gap adjustment in 0.05 mm steps - with digital gap display
- | TFT display with robust membrane keyboard
- | large, removable plastic funnel with smooth inner surfaces for easy cleaning and optimum material feeding
- | wear compensation of grinding disc thanks to zero point adjustment
- | Smooth inner surfaces of grinding chamber allow for easy and residue-free cleaning
- | additional labyrinth sealing seals the grinding chamber
- | easy change of grinding discs
- | optional version with polymer interior coating

FEATURES

Applications	preliminary and fine grinding
Field of application	chemistry / plastics, construction materials, engineering / electronics, geology / metallurgy, glass / ceramics
Feed material	medium-hard, hard, brittle
Size reduction principle	pressure, friction
Material feed size*	< 20 mm
Final fineness*	< 50 µm
Speed at 50 Hz (60 Hz)	440 min ⁻¹ (528 min ⁻¹)
Material of grinding tools	zirconium oxide, hardened steel, tungsten carbide, manganese steel
Gap width setting	0.05 - 12 mm
Collector capacity	2.5 l
Drive	3-phase geared motor
Drive power	1.8 kW
Electrical supply data	different voltages
Power connection	3-phase
Protection code	IP 55
W x H x D closed	520 x 630 x 1050 mm
Net weight	~ 240 kg
Standards	CE

FUNCTION PRINCIPLE

In the DM 400 the feed material enters the dustproof chamber from the filling hopper and is fed centrally between two vertical grinding discs. A moving grinding disc rotates against a fixed one and draws in the feed material. The necessary comminution effects are generated by pressure and frictional forces. The progressively arranged grinding disc meshing first subjects the sample to preliminary crushing; centrifugal force then moves it to the outer regions of the grinding discs where fine comminution takes place. The processed sample exits through the grinding gap and is collected in a receiver. The gap width between the grinding discs is incremental adjustable and can be motor-driven adjusted during operation in the range between 0.1 and 5 mm.



WolfLabs

Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

www.wolflabs.co.uk

Tel : 01759 301142

Fax : 01759 301143

sales@wolflabs.co.uk

Please contact us if this literature doesn't answer all your questions.