

Rotor Beater Mill SR 300

General Information

The Rotor Beater Mill SR 300 is suitable for coarse and fine size reduction, either in batches or continuously. It can process dry, soft, medium-hard, organic and inorganic substances.

With its adjustable speed of 3,000 to 10,000 rpm the rotor beater mill SR 300 is intended for universal use: from sample preparation in laboratories up to preparing sample batches in pilot plants or production facilities. The grinding chamber, the feed hopper and the material inlet are completely made from high quality stainless steel.

Application Examples

bentonite, chemical products, coal, coke, drugs, feed pellets, fertilizers, food, graphite, gypsum, herbs, pharmaceutical materials, plant materials, plastics, powder coating, resins, rice, salts, seeds, soils, spices, sugar, ... , ...

Product Advantages

- suitable for batchwise operation of larger quantities
- high final fineness
- adjustable speed for different applications
- easy cleaning thanks to exchangeable push-fit grinding insert, rotor and cassette
- grinding chamber, feed hopper and material inlet and outlet of stainless steel
- optional grinding inserts 180° for grinding of hard-brittle materials by additional impact
- optional distance rotor to reduce frictional heat
- removable hopper for easy cleaning
- electric engine brake
- defined final fineness due to bottom sieves with aperture sizes from 0.08 - 10 mm
- central locking device
- wide range of accessories including various collection and feeding systems, rotors and sieves

Features

Applications	size reduction, deagglomeration
Field of application	agriculture, chemistry / plastics, construction materials, environment / recycling, food, geology / metallurgy, medicine / pharmaceuticals
Feed material	soft, medium-hard
Material feed size*	< 25 mm
Final fineness*	< 50 µm
Speed at 50 Hz (60 Hz)	3,000 .. 10,000 min ⁻¹





Rotor Beater Mill SR 300

Rotor peripheral speed	22 ..72 m/s
Types of rotors	standard / distance
Material of grinding tools	rotor and sieves of stainless steel
Sieve sizes	trapezoid holes 0.08 / 0.12 / 0.20 / 0.25 / 0.35 / 0.50 / 0.75 / 1.00 / 1.25 / 1.50 / 2.00 mm round holes 3.00 / 4.00 / 10.00 mm
Hinged hopper	removeable hopper
Dust extraction unit	optional cyclone
Collector capacity	5 l / optional: 30 l
Drive	3-phase motor
Electrical supply data	200 .. 240 V
Power connection	1-phase
Engine brake	yes, electric
Protection code	IP 54
Power consumption	2.5 kW
W x H x D closed	600 x 1200 x 700 mm (with base frame)
Net weight	~ 60 kg (with base frame)
Standards	CE

Please note:

*depending on feed material and instrument configuration/settings

Videolink

Function Principle

Size reduction and deagglomeration in the SR 300 are achieved by impact and shear effects. The feed material passes from the hopper into the center of the grinding chamber where it is crushed between the rotor, sieve and grinding inserts. As soon as the material is smaller than the aperture size of the sieve it enters the collecting receptacle. The quick-acting door lock ensures easy access to the grinding chamber for quick cleaning. With their motor brake (braking time < 0.5 s), safety switch, splashback and access barrier in the inlet and outlet areas, Rotor Beater Mills offer the highest degree of operating safety.

Order data

Rotor Beater Mill SR 300

with rotor, 240 mm filter hose and collecting receptacle (please order retaining frame, sieves and optional base frame separately)

20.752.0001

SR 300, 200-240 V, 50/60 Hz

22.824.0007

Base frame with wheels



Rotor Beater Mill SR 300

Retaining frames and ring sieves for SR 300

Retaining frame 360° of stainless steel

22.642.0004

Retaining frame 360°

Ring sieves 360° of stainless steel

02.407.0057

Trapezoid holes, 0.08 mm

02.407.0026

Trapezoid holes, 0.12 mm

02.407.0028

Trapezoid holes, 0.20 mm

02.407.0029

Trapezoid holes, 0.25 mm

02.407.0120

Trapezoid holes, 0.35 mm

02.407.0030

Trapezoid holes, 0.50 mm

02.407.0031

Trapezoid holes, 0.75 mm

02.407.0032

Trapezoid holes, 1.00 mm

02.407.0058

Trapezoid holes, 1.25 mm

02.407.0033

Trapezoid holes, 1.50 mm

02.407.0034

Trapezoid holes, 2.00 mm

02.407.0035

Round holes, 3.00 mm

02.407.0036

Round holes, 4.00 mm

02.407.0040

Round holes, 10.00 mm, for pre-grinding

Retaining frame 180° of stainless steel

02.143.0066

Retaining frame with grinding insert for sieves 180°

Sieves 180° of stainless steel

03.647.0081

Trapezoid holes, 0.08 mm

03.647.0039

Trapezoid holes, 0.12 mm

03.647.0040

Trapezoid holes, 0.20 mm

03.647.0041

Trapezoid holes, 0.25 mm

03.647.0395

Trapezoid holes, 0.35 mm

03.647.0042

Trapezoid holes, 0.50 mm

03.647.0043

Trapezoid holes, 0.75 mm

03.647.0044

Trapezoid holes, 1.00 mm

03.647.0045

Trapezoid holes, 1.25 mm

03.647.0046

Trapezoid holes, 1.50 mm

03.647.0047

Trapezoid holes, 2.00 mm

03.647.0048

Round holes, 3.00 mm

03.647.0049

Round holes, 4.00 mm

03.647.0053

Round holes, 10.00 mm, for pre-grinding

Cyclone-suction-combination for SR 300

22.935.0020

Cyclone unit incl. 5 litres collection receptacle (to be used with industrial vacuum cleaner)

22.935.0021

Cyclone unit incl. 30 litres collection receptacle (to be used with industrial vacuum cleaner)

22.748.0005

Industrial vacuum cleaner for mills, 230 V, 50/60 Hz



Rotor Beater Mill SR 300

(other electrical versions and spare filter bags available upon request)

Vibratory Feeder DR 100

incl. push-fit feed chute 75 mm, holder for push-fit feed chute , hopper 3.5 litres, holder for hopper and fixture

70.938.2003	DR 100, 220-240 V, 50 Hz
70.938.2004	DR 100, 220-240 V, 60 Hz
70.938.2005	DR 100, 200 V, 60 Hz
70.938.2006	DR 100, 200 V, 50 Hz

Additional items SR 300

22.717.0007	Distance rotor of stainless steel
22.717.0006	Rotor of stainless steel
22.187.0008	Ring-type filter for collecting receptacle 5 litres
22.748.0001	Dust filter clamping rings for ring-type filter, incl. 5 dust filters
22.524.0002	Dust filters for ring-type filter, 25 pieces
02.011.0038	Collecting receptacle, 5 litres, stainless steel
02.187.0020	Filter hose for collecting receptacle 5 litres, length 240 mm, incl. comfort flange
02.186.0037	Spare filter hose for 02.187.0020
22.003.0015	Collecting receptacle, 30 litres, plastic, incl. filter hose and comfort flange
02.186.0042	Spare filter hose for 22.003.0015
99.200.0024	IQ/OQ Documentation for SR 300



Wolflabs

Wolf Laboratories Limited

www.wolflabs.co.uk

Tel: 01759 301142

Fax: 01759 301143

sales@wolflabs.co.uk



Use the above details to contact us if this literature doesn't answer all your questions.

Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

