SLS Lab Pro Pipettes

Single Channel

- Ergonomic design ensuring light weight & soft plunger movement
- Click-stop system for volume selection
- Colour coded for easy identification
- Calibration confirms to EN-ISO 8655 with report enclosed with every pipette

Code	Channel	Volume Range, µL	Increment, µL
SLS4900	Single	0.1-2.5	0.01
SLS4902	Single	0.5-10	0.1
SLS4910	Single	2-20	0.1
SLS4904	Single	5-50	0.5
SLS4906	Single	10-100	0.5
SLS4912	Single	20-200	1
SLS4908	Single	100-1000	5
SLS4914	Single	500-5000	50
SLS4916	Single	1000-10000	100

Multichannel

- Smooth and light tip loading and ejection
- Leak free sealing of tips
- Manifold can rotate 360° for easy right or left hand operation
- Easily removable & fully autoclavable manifold

Code	Channel	Volume Range, µL
SLS4926	8	0.5 - 10
SLS4918	8	5 - 50
SLS4920	8	10 - 100
SLS4922	8	20 - 200
SLS4924	8	30 - 300
SLS4936	12	0.5 - 10
SLS4928	12	5 - 50
SLS4930	12	10 - 100
SLS4932	12	20 - 200
SLS4934	12	30 - 300

Wolf Laboratories Limited

www.wolflabs.co.uk

Wolflabs

Tel: 01759 301142 Fax:01759 301143 sales@wolflabs.co.uk

Use the above details to contact us if this literature doesn't answer all your questions.

Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.