

purite hp

compact water purification system, designed to guarantee a consistent supply of high quality pure water



The Purite HP is a compact unit designed to produce a consistent supply of $> 10\text{M}\Omega\text{.cm}$ water for HPLC, ion chromatography, atomic absorption, hydrogen generation, and clinical analyser feed.

Additional features

- Guaranteed $> 10\text{M}\Omega\text{.cm}$ water quality
- Remote Dispense Pod (Optional)
- Energy saving intelligent stand-by mode
- Dispense rate of up to 2 litres/min
- Water quality parameters, $\text{M}\Omega\text{.cm}$, $^{\circ}\text{C}$, flowrate displayed
- Selectable manual and volumetric dispense feature
- Internal microfiltration
- UV LED disinfection incorporated within the dispense head
- ECO option now available offering 50% recovery which equates to a significant reduction in water usage and waste
- WiFi enabled for remote monitoring and operation.



purite hp

compact water purification system, designed to guarantee a consistent supply of high quality pure water


common purite features

Our Purite range of water purification systems is compact, robust, simple to use and easy to maintain and available in five standard models: Analyst, HP, Purewater 300, Fusion and Neptune Ultimate.

Common features of all our Purite systems include:

- Space-saving, dependable, bench top or wall mounted systems
- RO Removes > 98% minerals and > 99% bacteria
- Choice of production rates up to 48 l/hr
- Optional external storage tanks up to 100 litres
- RO Boost pump fitted as standard
- Installation kit and all consumables included for first few months operation
- LCD colour touch screen panel
- Visual and audible alarms included
- Utilises carbon pre-treatment, RO and deionisation
- USB port to download event data and upload software updates
- Integral 20 litre storage as standard (excludes Neptune Ultimate)
- Semi-automatic clean cycle.

► purite hp process flow



technical specifications

Unit Specification	160	320
Width (mm)	440	560
Depth (mm)	750	750
Height (mm)	36	41
Max shipping weight (kg)	51	59
Installation requirements		
Power	Single Phase, 110-230V, +/- 10%, 50/60 Hz	
Feed water	Potable	
Maximum TDS (ppm)	1000	
Minimum inlet pressure - psi (bar)	30 (2.1)	
Maximum inlet pressure - psi (bar)	90 (6.2)	
Feed water temperature	1-35°C	
Product outputs*		
@ 10°C (l/hr)	14.4	30
@ 25°C (l/hr)	24	48

* Product outputs based on a feed water pressure of 4 bar

System Specification	
Pure water storage	20 litre storage tank as standard (External 50 & 100 litre tanks available)
Display panel	LCD – Colour touch screen
Pre-treatment cartridge	✓
Reverse osmosis	✓
Deionisation cartridge	✓
Internal filtration	Microfiltration
Point of use	UV / LED
UV lamp	✓*
Recirculation pump	✓
Ultrapure polishing cartridge	-

* External tank version only

Treated Water Specification	High Purity Dispense	Purified Water Storage Tank
Inorganics	> 10MΩ.cm	
pH*	Neutral	
Bacteria	< 1cfu/ml	
Organics – TOC (ppb)	< 20	
Particles	0.005µm	
Endotoxins	-	
DNases	-	
RNases	-	
Dispense modes	Latched - hold - volumetric	
Dispense flow rate	up to 2.0 l/min	

* pH of stored water may decrease due to absorption of free carbon dioxide



The application of these marks only confirm that the QMS have been approved by LR, they are not an endorsement by LR, of any products or services offered by SUEZ WPS



WolfLabs

Wolf Laboratories Limited

www.wolflabs.co.uk

Tel: 01759 301142

Fax: 01759 301143

sales@wolflabs.co.uk



Use the above details to contact us if this literature doesn't answer all your questions.

Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

