

SciQuip Incu C-Series LT-Series

- Capacity 90ltr – 430ltr
- Temp -10 to +65°C (LT-series)
- Fully programmable
- Electro-polished chamber & shelves
- Audible & visual alarms
- Password protection
- Inner glass door
- Window in door as standard
- 50mm port as standard
- Interior lamp as standard



The SciQuip Incu C-series cooled incubators incorporate a precise cooling system providing excellent temperature uniformity throughout making them ideal for any application requiring accurate below ambient temperature control. All parameters are displayed in the large LCD screen for fast easy operation and read-out together with a graphic program display. The SciQuip Incubators can store up to 9 programs of 18 steps, each program can be made to repeat from 1 to 99 times automatically. All C-Series and LT-Series incubators are fitted with lockable castor wheels.

Technical Specifications

Model	Incu-90C	Incu-160C	Incu-270C	Incu-430C	Incu-160LT	Incu-270LT	Incu-430LT
Capacity (ltrs)	90	160	270	430	160	270	430
Temperature range (°C)	+4 to +60	+4 to +60	+4 to +60	+4 to +60	-10 to +60	-10 to +60	-10 to +60
Temperature set division (°C)	+/-0.1	+/-0.1	+/-0.1	+/-0.1	+/-0.1	+/-0.1	+/-0.1
Temperature uniformity (°C)	+/- 1	+/- 1	+/- 1	+/- 1	+/- 1	+/- 1	+/- 1
Timer (mins)	999, continuous	999, continuous	999, continuous	999, continuous	999, continuous	999, continuous	999, continuous
Shelves supplied	2	2	2	2	2	2	2
Max shelves	4	6	8	10	6	8	10
Inner dimensions (mm)	400x400x550	500x500x650	600x600x750	700x645x950	500x500x650	600x600x750	700x645x950
Outer dimensions (mm)	530x540x1260	630x640x1360	730x740x1460	830x785x1660	650x680x1360	750x780x1460	850x820x1660
Packed dimensions (mm)	650x660x1430	750x760x1530	850x860x1630	950x905x1830	770x800x1530	870x900x1630	970x940x1830
Weight (kg)	68	98	130	180	98	140	185
Power V/Hz	220-230 50/60	220-230 50/60	220-230 50/60	220-230 50/60	220-230 50/60	220-230 50/60	220-230 50/60
Warranty	2yrs	2yrs	2yrs	2yrs	2yrs	2yrs	2yrs

The SciQuip Incu LT-series have all the features of the C-series with additional cooling capability from -10 to +65°C.



Wolflabs

Wolf Laboratories Limited

www.wolflabs.co.uk

Tel: 01759 301142

Fax: 01759 301143

sales@wolflabs.co.uk



Use the above details to contact us if this literature doesn't answer all your questions.

Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

