

SciQuip Ovens S-Series HT-Series



SciQuip Ovens

- Capacity 30ltr 230ltr
- Temp up to 300°C (HT-Series)
- Fully programmable
- Fan-assisted excellent temp uniformity
- Audible & visual alarms
- Password protection
- Large LCD screen
- Separate overheat safety protection
- Viewing window

SciQuip fan assisted drying ovens have been designed to suit all drying applications including aging, bonding, curing, drying glassware, baking, sterilizing, heat treating, annealing, stress relieving and stability testing. The standard S-series provide temperatures up to 200°C, while the high temperature HT-series go to 300°C.

The SciQuip ovens can store up to 9 programs of 18 steps, which can be set for multiple ramp/ soak cycles or for running one temperature and switching automatically to another for a given time. Each program can be made to repeat from 1 to 99 times automatically.

All S-Series ovens stand on feet, with the exception of the 210S, which is on lockable castor wheels. All HT-Series come with lockable castor wheels.






The SciQuip ovens were designed to provide accurate temperature uniformity with no overshoot, the microprocessor achieves precise environmental control and features the advantage of rapid recovery after door opening.

All parameters are displayed in the large LCD screen for fast easy read-out.

Control Panel





Technical Specifications

Model	Oven-30S	Oven-55S	Oven-110S	Oven-210S	Oven-80HT	Oven-140HT	Oven-230HT
Capacity Itrs	30	55	110	210	80	140	230
Temperature range (°C)	ambient +5 to +200	ambient +5 to +300	ambient +5 to +300	ambient +5 to +300			
Temperature set division (°C)	+/-0.5	+/-0.5	+/-0.5	+/-0.5	+/-0.5	+/-0.5	+/-0.5
Temperature uniformity (°C)	+/- 1 C						
Timer (mins)	99, continuous						
Shelves supplied	2	2	2	2	2	2	2
Max shelves	2	4	8	8	4	8	8
Inner dimensions (mm)	300x300x340	330x360x450	420x400x650	500x550x750	375x375x550	450x450x685	520x550x800
Outer dimensions (mm)	490x430x720	520x490x830	610x530x1030	690x680x1130	565x505x930	640x580x1065	710x680x1180
Packed dimensions (mm)	610x550x890	640x610x1000	730x650x1200	810x800x1390	685x625x1100	760x700x1235	830x800x1400
Weight (kg)	40	50	61	98	58	80	104
Power V/Hz	220-230 50/60	220-230 50/60	220-230 50/60	220-230 50/60	220-230 50/60	220-230 50/60	220-230 50/60
Warranty	2yrs						



Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

www.wolflabs.co.uk

Tel: 01759 301142

Fax: 01759 301143

sales@wolflabs.co.uk

Please contact us if this literature doesn't answer all your questions.