

# MF 36 XSafe

**Scotsman**  
Ice Systems

## Modular Ice Machine 200 kg

Item #:

Project:

Quantity:



### FEATURES

- Produces Flake Ice, extruded at a temperature just below 0°C, with 25% residual water content, hence very rich in moisture.
- Stainless steel "scotch-brite" finish; rounded corners for enhanced aesthetics and ergonomics; top cover in PS plastic.
- Removable side panels on all four sides to aid routine maintenance and servicing.
- Sturdy evaporator in stainless steel AISI304, auger in AISI430.
- State of the art ice Breaker in special alloy.
- Reduced-maintenance, self-lubricating gear-reducer.
- Oversized hermetic compressor.
- Electronic control board with self diagnostic and malfunction alarms.
- XSafe: natural sanitation system, integrated inside the ice maker and operating automatically 24/7 to keep equipment clean & safe.



MF 36  
Flake ice  
Residual water content 25%

### CONDENSING SYSTEM

Air cooled  
Water cooled

### REFRIGERANT GAS

R134a  
R404A

### VOLTAGE V/Hz/ph

230/50/1  
230/60/1

### RECOMMENDED BINS

Head	Bins		kg
MF 36	✓	<b>SB193</b>	129
	✓	<b>SB322</b>	168
	CBT30EFSD	<b>SB393</b>	181
	CBT30EFSD	<b>SB530</b>	243
	CBT42EFSD	<b>SB550</b>	252
	CBT48FMCD	<b>SB948</b>	406
	●	<b>SIS300</b>	137 + 73
	●	<b>SIS700</b>	137 + 73

### LEGEND:

- ✓ : Perfect combination between ice maker and bin
- : Ice chute cut-out performed upon installation
- CBTxxxxxxxx : need additional bin top

### CERTIFICATIONS



### OPERATING REQUIREMENTS

	Minimum	Maximum
Air temperature	10	43
Water temperature	5	38
Water pressure	1 bar (14 psi)	5 bar (70 psi)
Electrical voltage	-10%	+10%

**IMPORTANT NOTICE:**  
Models and specifications are subject to change without notice.  
This spec sheet is meant for commercial purpose only.  
For technical documentation please refer to our service manuals.

Modular Ice Machine 200 kg

# MF 36 *XSafe*


**Scotsman®**  
Ice Systems

## Modular Ice Machine 200 kg

Item #:

Project:

Quantity:



### UNIT DATA

Size (W x D x H) 563 x 536 x 531 mm

Net weight 49 kg

### SHIPPING DATA

Carton (W x D x H) 630 x 610 x 680 mm

Weight 56 kg

		24 h ice production kg °C Amb. / °C Water			Energy consumption (*)		Water usage (*)	Instant power	Compressor	Circuit wires	Max. fuse size
Version	Voltage	10°C/10°C kg	21°C/10°C kg	32°C/21°C kg	kWh/ 100 kg	kWh/ 24h	l/h	W	W	No. x Ømm²	A
MF 36 AS	230/50/1	200	195	155	12.5	19.3	7.0	900	3400	3 x 1.5	10
MF 36 WS	230/50/1	205	200	178	10.1	18.0	91.0	750	3400	3 x 1.5	10
MF 36 AS	230/60/1	200	195	155	13.5	21.0	6.5	950	1770	3 x 1.5	16
MF 36 WS	230/60/1	200	195	155	13.5	21.0	108.3	950	1770	3 x 1.5	16

(\*) Data refer to 32°C Amb. / 21°C Water temperature conditions



# Wolf Laboratories Limited

[www.wolflabs.co.uk](http://www.wolflabs.co.uk)

Tel: 01759 301142

Fax: 01759 301143

[sales@wolflabs.co.uk](mailto:sales@wolflabs.co.uk)



**Use the above details to contact us if this literature doesn't answer all your questions.**

**Pricing on any accessories shown can be found by keying the part number into the search box on our website.**

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

