

UVP GelSolo

Simplified Gel Documentation



UVP GelSolo

The UVP GelSolo is a compact, easy-to-use, stand-alone system for gel documentation. It is designed to acquire gel images easily and without any need for training. Thus, it is ideal for multi-user laboratories and practical trainings.

Gel documentation, or the gel imaging process, involves recording and measuring labeled nucleic acid and protein in various types of media such as agarose or acrylamide.

The UVP GelSolo streamlines this process with live view; all exposure time, zoom and aperture settings are displayed in real-time on the 11.6 inch screen. Saturation monitoring allows for easy capture of fully quantifiable images. The UVP GelSolo system includes a light-sensitive monochrome camera with a high resolution of 5 megapixels. A highly sensitive zoom lens allows for high-contrast image acquisition. The system is controlled by a touch screen with the intuitive VisionWorks image acquisition and analysis software.

UVP GelSolo

Streamlined Gel Documentation





All-in-one design for streamlined gel documentation

- High resolution 5.0 MP camera
- Lens is easily accessible for adjustment of aperture, zoom and focus
- Three-position filter tray with Ethidium Bromide filter; additional filters are available
- Epi-white and epi-blue LED lights enable a variety of gel imaging applications
- Large 11.6" touch screen with user-friendly software optimizes image capture and analysis
- Easy access data storage for saving images on the USB drive, to the system or network computer
- Unique viewing window allows UV-safe viewing of gels without opening the door
- Wide front door; safety switch turns the UV light off when the door is open
- Side access doors for gel repositioning and cutting while viewing the gel on the screen
- Compact design maximizes laboratory bench space
- Choice of Transilluminator – single, dual or triple wavelength UV Transilluminator models, and blue light models

Integrated VisionWorks Software with Touch Screen Simplicity

The system is controlled by a touch screen with intuitive image acquisition and analysis software.

Intuitive Software with easy access to capture controls:

The VisionWorks software on the UVP GelSolo is a powerful yet intuitive software for capturing gel images and analyzing them. The simple user interface enables easy access to auto and manual image capture modes under the Device tab. Exposure time can be adjusted with customizable exposure settings. Captured images are saved in TIFF or JPEG formats.


Extensive image enhancement and analysis tools:

Image enhancement and analysis features are included with all systems. Researchers can personalize their experiments and make use of enhancement features and annotation tools for publication purposes. The software offers many powerful tools such as noise reduction, histogram adjustment, inversion, pseudocolor, and more.

The extensive analysis features are optimized for accurate and reproducible results. Several custom tools are available, such as automatic lane and band detection, 1D analysis, area density, and colony counting. Once the quantitation results have been generated, reports are created to show thorough analysis, such as Molecular Weight (MW), Rf, band intensities, and area density calculations. All the data can be conveniently exported to Excel.

Choice of switching to an advanced software interface:

Users can swiftly switch to an advanced version of the user interface by selecting 'Advanced' UI under the About tab in the Settings menu. The advanced version offers additional features such as Stacks and Series capture modes under the Device tab, a preloaded list of preset 'Actions' (automated workflow templates) for common gel imaging applications, image enhancement tools such as background subtraction and compositing, and more.



Optimized Gel Documentation and Analysis

The main application of the UVP GelSolo is saving and printing gel images. VisionWorks software allows for gel analysis.

Easily switch between emission filters

The three-position emission filter tray can be used to place three different filters and switch between them for different applications. An Ethidium Bromide filter is included with the system, but a variety of other emission filters are available for additional purchase.

Transilluminators

Seven different UV Transilluminator options are available based on filter size and UV wavelength (Filter sizes: 20 x 20cm, 21 x 26cm or 25 x 26cm; Wavelength: 1UV 302nm, 2UV 302/365nm or 3UV 254/302/365nm, 100-115V/60Hz or 230V/50Hz). A blue light transilluminator is also available.

Converter plates

For blue light excitation of fluorescent dyes such as SYBR Green, a Visi-Blue converter plate can be used as an economical alternative to the blue light transilluminator. Imaging of non-fluorescent gels (e.g. silver or Coomassie Blue stained polyacrylamide gels) can be done using the Visi-White converter plate. This plate converts the UV light to visible light, similar to the light of a white light table. In addition, a UV to long-wave UV converter plate can be used to reduce the risk of damaging DNA during gel excision. All the converter plates are meant to be directly placed on top of a UV transilluminator.



Visi-Blue and Visi-White Converter Plates



Maximum UV Protection for Users

We prioritize UV protection, ensuring safe operation for all users.

Opening the front door of the UVP GelSolo automatically switches off the UV light. A UV-safe gel viewing window in the front door allows a direct and safe view to the fluorescent gel under UV illumination for visual control. For cutting gels under UV illumination, two side-access doors are included.

For cutting fragments from a gel while the main door is opened, a UV override switch allows users to deactivate the safety switch-off. Closing the door automatically re-activates the UV protection switch. This ensures safe operation for subsequent users.




Technical Data


Specifications/features	UVP GelSolo
Camera/Lens	GelCam 315, 5.0 MP, with 8-48mm, f/1.2 manual zoom lens
Darkroom features	<ul style="list-style-type: none"> ▪ 11.6" large articulating touch screen ▪ Wide front door with UV safety switch ▪ Gel viewer window ▪ Epi white and epi blue LEDs ▪ Side access doors ▪ USB ports ▪ 3-position emission filter tray
Accessories included	<ul style="list-style-type: none"> ▪ Ethidium bromide filter ▪ Choice of UV transilluminator (Filter sizes: 20 x 20cm, 21 x 26cm or 25 x 26cm; Wavelength: 1UV 302nm, 2UV 302/365nm or 3UV 254/302/365nm, 100-115V/60Hz or 230V/50Hz), or blue light transilluminator
Dimensions: H x W x D	80.5 x 39.4 x 38.4 cm (31.7 x 15.5 x 15.1 inch)

Applications


- Fluorescent DNA gels
- Fluorescent protein gels
- Colorimetric protein gels



Ethidium bromide stained agarose gel
(UV light)



Silver stained polyacrylamide gel
(white light)



Ethidium bromide stained agarose gel
(UV light)

Order Information

Order number		Description	
230 V	115 V	UVP GelSolo	Transillumimnator
849-97-0934-02	849-97-0934-01	UVP GelSolo, M-20V	20 x 20cm, 302nm
849-97-0935-02	849-97-0935-01	UVP GelSolo, M-26V	21 x 26cm, 302nm
849-97-0936-02	849-97-0936-01	UVP GelSolo, M-26XV	25 x 26cm, 302nm
849-97-0937-02	849-97-0937-01	UVP GelSolo, LM-20	20 x 20cm, 302/365nm
849-97-0938-02	849-97-0938-01	UVP GelSolo, LM-26	21 x 26cm, 302/365nm
849-97-0939-02	849-97-0939-01	UVP GelSolo, LMS-20	20 x 20cm, 254/302/365nm
849-97-0940-02	849-97-0940-01	UVP GelSolo, LMS-26	21 x 26cm, 254/ 302/365nm
		Accessories	
849-95-0611-01		Blue LED Transilluminator	
849-00401-0		Emission filter, 50 mm square, with transmission range 510 - 560 nm, for e.g. SYBR® Green stains	
849-00402-0		Emission filter, 50 mm square, with transmission range 520 - 620 nm for e.g. SYBR® Gold stains	
849-20510-0		UVP Visi-White Converter plate, UV-to-white, 21 cm x 26 cm filter size	
849-20511-0		UVP Visi-White Converter plate, UV-to-white, 25 cm x 26 cm filter size	
849-20520-0		UVP Visi-Blue Converter plate, UV-to-blue, 21 cm x 26 cm filter size, 460 nm - 470 nm	
849-20521-0		UVP Visi-Blue Converter plate, UV-to-blue, 25 cm x 26 cm filter size, 460 nm - 470 nm	

Headquarters

Your Regional Partner

Analytik Jena US

Pictures: Analytik Jena US

Subject to changes in design and scope of delivery as well as further technical development.

en - 03/2018
© Analytik Jena AG



Wolf Laboratories Limited

www.wolflabs.co.uk

Tel: 01759 301142

Fax: 01759 301143

sales@wolflabs.co.uk



Use the above details to contact us if this literature doesn't answer all your questions.

Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

