Equinox Analytical and Semi-Micro Balances





Equinox analytical balances bring remarkable precision to labs that perform highly detailed testing. The Equinox is ideal for research and quality assurance facilities; science education; precision counting; and production and manufacturing applications needing exceptionally precise results. A color touch screen display provides intuitive operation, with icon-driven menus and readily accessible applications and functions.

Versatile and resilient, Equinox provides intuitive operation and readily accessible functions



Features

- Large, responsive 5" 800x480 pixel touch-screen display
- · Level indicator and adjustable feet ensure proper balance setup for optimum weighing
- Security slot for optional Kensington-type lock and cable to help prevent theft
- Large, grade 304 stainless steel pan allows easy cleaning
- · RS-232 interface is available to provide speedy connection to computers and printers
- · USB host for memory card
- Built-in memory for storing products and settings
- · External calibration allows for verification and adjustment with weights
- Selectable digital filtering helps minimise effects of vibration and disturbances
- Security password control prevents unauthorised access
- Printouts include date and time for data tracking within Good Laboratory Practices
- Preset tare function speeds the process of repetitive weighing
- Parts counting with freely selectable sample sizes
- Multilingual display allows use in many different countries
- Memory accumulation totals results
- Checkweighing with audible alarm
- · AC adapter included

Applications

- · Weighing
- · Parts counting
- · Percentage weighing
- Checkweighing
- · Dynamic / animal weighing
- · Accumulation of weight
- · Density determination
- · Display hold
- Formulation
- Statistics
- · Textile

About ADAM:

For more than 40 years, professionals worldwide have relied on Adam Equipment for an extensive selection of dependable and affordable weighing equipment. Adam provides the right balance of speed, performance and value.

Equinox Analytical and Semi-Micro Balances **EXELADAM**



| Model | EAB 125i | EAB 225i | EAB 124e | EAB 224e | EAB 314e | EAB 124i | EAB 224i | EAB 314i | EAB 414i | EAB 514i |
|-------------------------------|---|---------------|----------------------|----------|----------|--------------------------------|----------|----------|----------|----------|
| Capacity | 62g / 120g | 82g / 220g | 120g | 220g | 310g | 120g | 220g | 310g | 410g | 510g |
| Readability | 0.01mg/ 0.1mg | 0.01mg/ 0.1mg | 0.0001g | 0.0001g | 0.0001g | 0.0001g | 0.0001g | 0.0001g | 0.0001g | 0.0001g |
| Repeatability (S.D.) | 0.02mg/ 0.1mg | 0.02mg/ 0.1mg | 0.0002g | 0.0002g | 0.0002g | 0.0002g | 0.0002g | 0.0002g | 0.0002g | 0.0002g |
| Linearity (+/-) | 0.1mg / 0.2mg | 0.1mg / 0.2mg | 0.0003g | 0.0003g | 0.0003g | 0.0003g | 0.0003g | 0.0003g | 0.0003g | 0.0003g |
| Minimum Weight (USP, typical) | 60mg | 100mg | 200mg | 200mg | 200mg | 200mg | 200mg | 200mg | 700mg | 700mg |
| Pan Size | 3.1" ø / 80mm ø | | | | | | | | | |
| Weighing Units | g, mg, ct, GN, lb, oz, dwt, mm, ozt, tl.H, tl.S, tl.T, T, custom unit | | | | | | | | | |
| Stabilization Time (sec) | 6 | | 4 | | | | | | | |
| Interface | RS-232, USB | | | | | | | | | |
| Calibration | Internal automatic calibration | | External calibration | | | Internal automatic calibration | | | | |
| Display | Touchscreen with 4.9"/ 125mm -high digits | | | | | | | | | |
| Power Supply | 24V 50/60Hz 500mA adapter | | | | | | | | | |
| Operating Temperature | 10° to 30°C / 50° to 86°F | | | | | | | | | |
| Housing | ABS plastic | | | | | | | | | |
| Draft Shield | Chamber 7.6"x7.7"x9.1" / 192x195x230mm | | | | | | | | | |
| Overall Dim. | 8.8"x14.7"x13.3" / 224x374x338mm (wxdxh) | | | | | | | | | |
| Net Weight | 15.9lb / 7.2kg | | | | | | | | | |

Accessories

| Item number | Description |
|-------------|--|
| 104008036 | Anti-vibration table |
| 1060014262 | Density kit |
| 3012014259 | In-use cover |
| 1120011156 | ATP thermal printer |
| 3126011263 | ATP thermal printer paper |
| 3126011281 | ATP thermal printer paper (pack of 10) |
| 3014011014 | RS-232 cable M-F |
| 700100046 | Kensington-type lock and cable |
| 600002028 | AdamDU Data Collection |
| 700660290 | Calibration certificate |
| 700100410 | ABI-1 loniser |
| 700100398 | E1 5g Calibration Weight |
| 700100399 | E1 10g Calibration Weight |
| 700100400 | E1 20g Calibration Weight |
| 700100401 | E1 50g Calibration Weight |
| 700100022 | E2 100g Calibration Weight |
| 700100023 | E2 200g Calibration Weight |
| 700100419 | E1 1mg - 50g Calibration Weight Set |
| 700100420 | E1 1mg - 100g Calibration Weight Set |
| 700100421 | E1 1mg - 200g Calibration Weight Set |
| 700100026 | E2 1mg - 200g Calibration Weight Set |
| 700100207 | E2 1g to 200g Calibration Weight Set |

Key Accessories



ATP thermal printer

Easy-to-use features combined with quick set-up equals a truly versatile thermal printer. A single push-button feed key and three easy-to-read LED indicators make operation simple.



AdamDU data collection program

Adam DU software connects a balance to the laboratory network, helping to achieve seamless data collection, transfer and analysis. DU features an easy-to-use interface with a main command window, allowing users to quickly collect information from up to eight Adam balances simultaneously using RS-232 or USB connections.

Supplied by



Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

www.wolflabs.co.uk

Tel: 01759 301142

Fax: 01759 301143

sales@wolflabs.co.uk

Please contact us if this literature doesn't answer all your questions.