

- Accurate temperature control from 0°C to 60°C
- Powerful compressor, maintains 0°C
- Stainless-steel internal chamber
- Internal power inlet for shakers, mixers, etc.
- Sized for floor standing use or on bench-tops (less than 32" tall)



Stainless-steel chamber with internal outlet & light

The myTemp 65HC Incubator is designed to provide accurate and uniform temperature control from 0 to 60°C. The broad temperature range of the instrument expands the use of this incubator to both heating and cooling applications.

A large, digital display allows for visualization of the chamber temperature and the remaining incubation time, while an internal light is included for improved visualization of the chamber. In addition, a built in, internal outlet can be used to provide power to small instruments, such as shakers, rockers, etc.

With forced air technology and stainless steel inner construction, uniform heat transfer is ensured throughout the internal chamber. When set for sub-ambient temperatures, the powerful compressor is activated, quickly cooling the chamber to the desired temperature.

With an exterior height of 39 inches (100cm), the incubator is designed to be floor-standing, yet is also compact enough for bench-use. (Not recommended for use on benchtops taller than 32"/81cm). The instrument is supplied with two, adjustable height shelves, while additional shelves can also be purchased separately (item: H2265-SH).

## **Technical Data**

Temp. Range: 0°C to 60°C (RT-25°C to 60°C) Temp. Accuracy: 0.5°C (at 37°C) Temp. Uniformity: +/- 1.0.°C (at 37°C)

all Hill Harin

Temp. Increments: 0.1°C

Dimensions:

21.25 x 21 x 39.35 in.

Exterior: (WxDxH) 54 x 53.34 x 99.85 cm 15.75 x 12.75 x 19.75 in. Interior: 40 x 32.4 x 50.2 cm

Capacity: 65L or 2.3 cubic feet 117 lbs (53kg) Weight:

120V, 60Hz or 230V, 50Hz\* (385W) Electrical:

Warranty: 2 years

## **Ordering Information:**

H2265-HC\* MyTemp™ 65 Heating and Cooling

**Incubator**, includes two stainless steel shelves

H2265-SH Extra shelf, stainless steel

\* 115V with US plug. For 230V (EU plug), please add (-E)





Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

## www.wolflabs.co.uk

Tel: 01759 301142

Fax: 01759 301143

sales@wolflabs.co.uk

Please contact us if this literature doesn't answer all your questions.