



Sticky Step Plastic

Sticky Step Plastic has been designed to help prevent contamination from entering controlled working environments. The mat features an anti-microbial adhesive surface which helps remove dust and dirt from footwear or wheeled trolleys. Sticky Step Plastic is formed of 30 peel-off layers, making it perfect for maintaining clean room and laboratory standards. The overall thickness is 2mm and the bottom of the mat securely adheres to any clean, dry surface. Sold in packs of four, Sticky Step Plastic can be used for a wide variety of applications, from data centres, medical, pharmaceutical, electronics, aerospace, instrumentation, nuclear to construction environments.

Features

- ◆ **Typical applications:** Perfect for maintaining clean room and laboratory standards. Can also be used for operating theatres, intensive care units, data centres and pharmaceutical, electronics, aerospace, instrumentation, nuclear and construction environments.
- ◆ **Material:** Polyethylene film coated with acrylic (water solvable) adhesive.
- ◆ **Cleaning:** Simply peel off the top layer to reveal a clean layer below.
- ◆ **Warranty:** Lifetime.



Suitable for indoor use



For more information about this product or, to place an order [click here](#)



Code	Metric	Imperial	Thickness	Weight	Per	Colour
SP1845BU	48cm x 110cm	2' x 4'	2mm	5.5kg	(pack of 4)	Blue
SP1845WH	48cm x 110cm	2' x 4'	2mm	5.5kg	(pack of 4)	White
SP2436BU	60cm x 90cm	2' x 3'	2mm	5.9kg	(pack of 4)	Blue
SP2436WH	60cm x 90cm	2' x 3'	2mm	5.9kg	(pack of 4)	White
SP3660BU	90cm x 150cm	3' x 5'	2mm	14.7kg	(pack of 4)	Blue
SP3660WH	90cm x 150cm	3' x 5'	2mm	14.7kg	(pack of 4)	White

Please note, the width/length can be +/- 2%

Please note, all Imperial sizes have either been rounded up or down to the nearest whole number

Our delivery promise

We guarantee your order will be shipped on time, every time.
That's the Blue Diamond difference.

Sticky Step Plastic

Technical Specification

Slip resistant:	Great slip resistance to level 2
Wear resistant:	Great wear resistance to level 2, suitable for medium to high footfall
Anti-microbial:	Yes, contains 2-n-octyl-4-isothiazolin-3-one (OIT)
Disability friendly:	Yes, the low profile makes it suitable for wheelchair users
Dry area:	Yes
Wheeled area:	Yes
Medical area:	Yes
Environment:	Suitable for indoor use
Product testing:	<ul style="list-style-type: none">◆ Peel adhesion in accordance with CSN EN ISO 1939 0,48 (N/10mm)◆ Tensile strength (LD) in accordance with CSN EN ISO 527-1.3 - 28 MPa (+-0,7)◆ Tensile strength (TD) in accordance with CSN EN ISO 527-1.3 - 18,3MPa (+-0,6)
Cleaning:	Simply peel off the top layer to reveal a clean layer below



WolfLabs

Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

www.wolflabs.co.uk

Tel : 01759 301142

Fax : 01759 301143

sales@wolflabs.co.uk

Please contact us if this literature doesn't answer all your questions.