

## NE2D Series Unstirred Digital Water Baths



The **NE2D series** provides a stable temperature environment ideal for meeting quality control requirements, featuring digital PID temperature control for precision. Controls feature auto alarm setting, illuminated on/off switch, heater and over temperature indications.

Comprising of a high quality corrosion resistant stainless steel tank, with a bright clean finish housed in a durable painted outer case. Painted surfaces feature anti-bacterial finish with good chemical resistance.

|                         | NE2 - 4D   | NE2 - 8D           | NE2 - 10D          | NE2 - 14D          |
|-------------------------|--|--------------------|--------------------|--------------------|
| <b>GENERAL</b>          |  |                    |                    |                    |
| Temp. Range             | Ambient + 5°C - 100°C  |                    |                    |                    |
| Temp. Alarm             | Over temperature alarm is automatically set 4°C above set point              |                    |                    |                    |
| Temp. Control           | PID Digital, LED display showing actual or set temperature, resolution 0.1°C |                    |                    |                    |
| Sensitivity/Uniformity  | ±0.2°C / ±0.1°C  |                    |                    |                    |
| Heater Power (220-240V) | 400W   | 800W               |                    | 1000W              |
| Voltage                 | 120V or 230V models available 50-60Hz  |                    |                    |                    |
| <b>DIMENSIONS</b>       |  |                    |                    |                    |
| Tank Capacity           | 4 Litre  | 8 Litre            | 10 Litre           | 14 Litre           |
| External (mm)           | 332w x 185d x 290h   | 332w x 270d x 290h | 332w x 270d x 290h | 361w x 332d x 290h |
| Internal (mm)           | 300w x 150d x 150h   | 300w x 240d x 150h | 300w x 240d x 200h | 325w x 300d x 150h |
| Water Level Max. (mm)   | 130  |                    | 180                | 130                |
| Water Level Min. (mm)   | 55   |                    |                    |                    |

|                         | NE2 - 22D  | NE2 - 28D          | NE2 - 56D          |
|-------------------------|--|--------------------|--------------------|
| <b>GENERAL</b>          |  |                    |                    |
| Temp. Range             | Ambient + 5°C - 100°C  |                    |                    |
| Temp. Alarm             | Over temperature alarm is automatically set 4°C above set point              |                    |                    |
| Temp. Control           | PID Digital, LED display showing actual or set temperature, resolution 0.1°C |                    |                    |
| Sensitivity/Uniformity  | ±0.2°C / ±0.1°C  |                    |                    |
| Heater Power (220-240V) | 1500W  |                    | 2500W              |
| Drain (12mm Bore)       | Drain Outlet   |                    |                    |
| Voltage                 | 120V or 230V models available 50-60Hz  |                    |                    |
| <b>DIMENSIONS</b>       |  |                    |                    |
| Tank Capacity           | 22 Litre   | 28 Litre           | 56 Litre           |
| External (mm)           | 538w x 332d x 290h   | 538w x 332d x 290h | 660w x 540d x 290h |
| Internal (mm)           | 500w x 300d x 150h   | 500w x 300d x 200h | 620w x 500d x 200h |
| Water Level Max. (mm)   | 130  | 180                |                    |
| Water Level Min. (mm)   | 55   |                    |                    |

Accessories on Page 14-17



# WolfLabs

**Pricing on any accessories shown can be found by keying the part number into the search box on our website.**

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

**[www.wolflabs.co.uk](http://www.wolflabs.co.uk)**

**Tel : 01759 301142**

**Fax : 01759 301143**

**[sales@wolflabs.co.uk](mailto:sales@wolflabs.co.uk)**

Please contact us if this literature doesn't answer all your questions.