

## Three-Dimensional Shaker TL 10



### Description

The Three-Dimensional Shaker TL 10 works with slow, three-dimensional motion. The angle of tilt is adjustable between 0° and 9° and the shaking speed between 1 and max. 23 rpm. The shaking platform of 340 x 340 mm can be loaded with max. 10 kg.

### Basic Equipment

Basic device incl. basic tray and rubber mat

### Details

<b>Motion:</b>	three-dimensional orbital motion
<b>Shaking platform:</b>	340 x 340 mm
<b>Max. load:</b>	10 kg
<b>Shaking speed:</b>	1 - 23 rpm, steplessly adjustable

**Angle of tilt:** 0° to 9° einstellbar  
**Timer:** 0 - 120 min / continuous  
**Order No.:** 6117 000  
**Accessory:** Multi-storey rack system WS / TL

## Technical specifications

**Electrical supply:** 230 V or 115 V, 50 / 60 Hz please indicate in case of order  
**Enclosure protection:** IP 21  
**Heat emission:** approx 7 - 10 W  
**Ambient temperature::** 5°C to 50°C  
**Relative humidity:** ~ 85 %  
**Dimensions (w x d x h):** 355 x 450 x 205 mm  
**Weight:** 18,5 kg



# WolfLabs

**Pricing on any accessories shown can be found by keying the part number into the search box on our website.**

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

**[www.wolflabs.co.uk](http://www.wolflabs.co.uk)**

**Tel : 01759 301142**

**Fax : 01759 301143**

**[sales@wolflabs.co.uk](mailto:sales@wolflabs.co.uk)**

Please contact us if this literature doesn't answer all your questions.