

# Three-Dimensional Shaker TL 2



## Description

The Laboratory Shaker TL 2 works with slow, three-dimensional motion for gentle, uniform wetting. Well suited for petri dishes, culture bottles etc.

### Basic Equipment

Basic device incl. basic tray and rubber mat

## Details

**Motion:** three-dimensional orbital motion  
**Shaking platform:** 220 x 220 mm  
**Max. load:** 2 kg

**Shaking speed:** 1 - 22 rpm, steplessly adjustable  
**Angle of tilt:** 8° fixed  
**runtime:** 0 - 9 h 59 min / continuous  
**Order No.:** 6139 000  
**Accessory:** Additional Tray TL 2

## Technical specifications

**Electrical supply:** 100 - 240 V, 50 / 60 Hz  
**Enclosure protection:** IP 21  
**Heat emission:** max. 3 W  
**Ambient temperature::** 5°C to 45°C  
**Relative humidity:** ~ 85 %  
**Dimensions (w x d x h):** 250 x 415 x 118 mm  
**Weight:** 9,1 kg



# WolfLabs

**Pricing on any accessories shown can be found by keying the part number into the search box on our website.**

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

**[www.wolflabs.co.uk](http://www.wolflabs.co.uk)**

**Tel : 01759 301142**

**Fax : 01759 301143**

**[sales@wolflabs.co.uk](mailto:sales@wolflabs.co.uk)**

Please contact us if this literature doesn't answer all your questions.