

Multi-Flask Shaker VKS 75 A control



Description

Big heavy-duty shaker VKS 75 A control with digital display and programmable control has an orbital shaking motion, a speed range of 30 – 200 rpm and a stroke of 26 mm. The VKS 75 A control is ideally suited for high loads up to 75 kg. **(floor installation only!)**

Basic Equipment

Basic device without shaking plate, without rack system With digital display and programmable control

Loading Capacity

Erlenmeyer flasks 500 ml 32 pieces Erlenmeyer flasks 2000 ml 12 pieces Separating funnels 1000 ml 6 pieces

You will find further loading possibilities here

Loading details against shaking speed

Option:

<u>Control interface</u> <u>USB interface</u>

Details

Motion: orbital

Shaking platform: 760 x 600 mm

Max. load: 75 kg

Shaking Speed: 30 - 200 rpm, in steps of 5

Stroke: 26 mm

Runtime: programmable / continuous

Order no.: 6111 000

Accessory: Shaking plate VKS (1-storey)

> Rack System Combifix VKS A Rack System Combifix VKS B Rack System Combifix VKS C Universal tray VKS 1-storey Rack System VKS (2-storey)

Rack System VKS "Giant" (3-storey)

Technical specifications

Electrical supply: 100 - 240 V, 50 / 60 Hz please indicate in case of order

Enclosure protection: IP 21

Heat emission: max. 45 W **Ambient temperature:** 5°C to 50°C

Relative humidity: ~ 85 %

Dimensions (w x d x h): 1050 x 835 x 250 mm

Weight: 110 kg



Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

www.wolflabs.co.uk

Tel: 01759 301142

Fax: 01759 301143

sales@wolflabs.co.uk

Please contact us if this literature doesn't answer all your questions.