

# IKA

designed for scientists



## VXR basic Vibrax®

/// Data Sheet

Optoelectronically controlled small shaker with a very wide speed range (0 - 2200 rpm).

- Suitable for continuous operation
- New design and improved drive system
- Circular shaking motions
- Slow speeds are well maintained
- Attachments are interchangeable



designed for scientists

### Technical Data

Type of movement	orbital
Shaking stroke [mm]	4
Permissible shaking weight (incl. attachment) [kg]	2
Motor rating input [W]	35
Motor rating output [W]	13.2
Permissible ON time [%]	100
Speed min (adjustable) [rpm]	100
Speed range [rpm]	0 - 2200
Speed display	scale
Operating mode	continuous operation
Dimensions (W x H x D) [mm]	157 x 130 x 247
Weight [kg]	6.1
Permissible ambient temperature [°C]	5 - 40
Permissible relative humidity [%]	80
Protection class according to DIN EN 60529	IP 21
Voltage [V]	220 - 240
Frequency [Hz]	50/60
Power input [W]	45



# WolfLabs

**Pricing on any accessories shown can be found by keying the part number into the search box on our website.**

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

**[www.wolflabs.co.uk](http://www.wolflabs.co.uk)**

**Tel : 01759 301142**

**Fax : 01759 301143**

**[sales@wolflabs.co.uk](mailto:sales@wolflabs.co.uk)**

Please contact us if this literature doesn't answer all your questions.