KERN OIV 345



The entry level video microscope with bright image reproduction and intuitive operation



Category	
Brand	Optics
Product categoriy	Microscope
Product group	Video microscope
Product family	OIV-3
Display	

Display type	LCD
Display screen size	12"
Display resolution	1920×1080 HD
Languages of the user interface	German English French Spanish Italian Russian

Construction	
Dimension (W×D×H)	320×260×450 mm
Dimension display device (W×D×H)	275×170×12 mm
Material display housing	Plastics
Optical system	Axial
Tube type	Trinocular
Contrasting methods	Bright field

E	nct	•	
	пст	Inr	18
I U	1100	101	10

Camera - Applicable software	integrated
Camera - Software functions	Image capturing Video capturing Image editing/ Documentation Measurements
Memory - total size	32 GB

Interface	
Interfaces	USB 2.0 HDMI MicroSD card slot
Objective	
Objectives magnifications	0,7 x - 4,5 x
Illumination	
Illuminance	Reflected light
Illumination type incident light	LED
Illumination intensity incident light	3 W
Illumination dimmable	Incident light
Focussing	
Field of view [Min]	2,5 mm
Field of view [Max]	16 mm
Zoom [Min]	0,7 x
Zoom [Max]	4,5 x
Sample height [Max]	110 mm
Working distance	100 mm
Magnification ratio	6,4:1
Focusing mechanism	coarse drive
Stereomicroscope stand	
Stand type	mechanical
Camera	
Cameratype	integrated tablet-camera
Camera - Resolution	5 MP
Camera - Sensor type	Sony CMOS
Camera - Sensor size	1/2,8"
Camera - Framerate	60 fps
Camera - Exposure method	Rolling Shutter
Power Supply	
Supplied power supply	Power supply unit
Plug-in power supply type	Table power supply (separable)
Plug-in power supply / adapter for countries - included with the delivery	EURO
Plug-in power supply / adapter for countries - optional	EURO UK US CH

KERN OIV 345



The entry level video microscope with bright image reproduction and intuitive operation

Input voltage power supply /	100 V - 240 V, 50 / 60
power [Max]	Hz
Input voltage device / power [Max]	12 V, 2000 mA
Environmental conditions	
Storage temperature [Min]	-5 °C
Storage temperature [Max]	40 °C
Approval	
CE mark	1
CE mark	✓
CE mark Packing & Shipping	✓
	✓ 1 d
Packing & Shipping	
Packing & Shipping Delivery time	1 d
Packing & Shipping Delivery time Dimensions packaging (W×D×H)	1 d 420×390×250 mm
Packing & Shipping Delivery time Dimensions packaging (W×D×H) Shipping method	1 d 420×390×250 mm Parcel service
Packing & Shipping Delivery time Dimensions packaging (W×D×H) Shipping method Net weight approx.	1 d 420×390×250 mm Parcel service 4,4 kg

Pictograms

STANDARD





Pricing on any accessories shown can be found by keying the part number into the search box on our website. The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

www.wolflabs.co.uk

Tel : 01759 301142 Fax : 01759 301143 sales@wolflabs.co.uk

Please contact us if this literature doesn't answer all your questions.