Laboratory Essential Freezer

98L Laboratory Essential Spark-free Freezer

GDMAcode LSFSF110

SKU code 444411345





Key features

- √ Spark-free interior to reduce risk of ignition
- ✓ Lockable door with two keys



Spark-free

We have removed items such as fans and lights so the interior of the fridge has no chance of igniting flammable liquids.



Secure Fitted Lock

Integrated door lock, comes with two keys for added security to keep contents safe.

Specification: 98L Laboratory Essential Upright Freezer with Solid Door

, , ,	
Gross Capacity (litres)	98L
Net Capacity (litres)	84L
Unit External Width (mm)	595mm
Unit External Depth (mm)	660mm
Unit External Height (mm)	850mm
Product Weight (kg)	37.25Kg
Packed Width (mm)	640mm
Packed Depth (mm)	
Packed Height (mm)	910mm
Packed Weight (kg)	41.75Kg
Country of Origin	UK
Internal Dimensions (mm) (WxDxH)	445mm x 290mm x 160mm
Temperature Range	-18°C to -25°C
Colour	White
External Finish	Painted Steel
Internal Finish	HIPS
Type of plastic	SRL800 (HIPS/ABS mix)
Door Finish	Painted Steel / Solid
Door Type	Solid
Door Type Door Style	Hinged, Right
Door Liner	
	Flat
Number of Door Trays	n/a /-
Number of Door Tray Positions	n/a
Door Open Depth (mm)	1150mm
Replacement Door Seal	Yes
Open Door Sensor	Yes
Lock	Yes, 2 Keys
Adjustable Feet (number & position)	4 All adjustable
Porthole	No
Porthole Size	n/a
Porthole Location	n/a
Temperature Display on Panel	No
Temperature Alarm	No
Remote Alarm Contacts	No
Audible Alarms	No
Visual Alarms	No
Number of Shelves/Drawers	3
Number of Shelf Positions	3
Shelf Size (mm) (WxDxH)	495mm x 325mm x 6mm
Shelf Material	Glass/HIPS
Drawer Size (mm) (WxDxH)	2@ 385mm x 395mm x 195mm, 1@ 385mm x 242mm x 205mm
Drawer Material	HIPS*
Interior Light	No
Light Type	n/a
Light Activation	n/a
Fan	No
Spark Free	Yes
Defrost setting	Auto (Off Cycle)
Controller Type	Digital, External
Battery Back Up/Hours	No
Bluetooth	No No
Number of Probes	0
Probe Type	10°C to 32°C
Ambient Temperature Range	
Refrigerant Type	R600a
Voltage Supply (v)	220-240V
Insulation Thickness (mm)	80mm
	Little Danaster Dalumathana - Faran
Insulation Type	High Density Polyurethane Foam
Blowing Agent	Cyclopentane



Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

www.wolflabs.co.uk

Tel: 01759 301142

Fax: 01759 301143

sales@wolflabs.co.uk

Please contact us if this literature doesn't answer all your questions.