Chest freezer XLT C75



- Low cost of ownership
- Limited maintenance and on-site service
- Easily installable & movable

- Efficient cyclopentane insulation
- Eco-friendly, HCFC-free Nature R refrigerant
- ISO 9001, 14001 & 18001 OHSAS Certified

Specifications

Technical

Gross volume 74 litres 71 litres Net Volume -45°C to -65°C Temp. range Temp. probes 1/PT 1000 Compressor Secop Baskets (incl./optional) 1/1 Refrigerant Nature R 55 dB Noise level 4,0 kWh Power consumption 24/h 1.460 kWh/year Power consumption 230V Voltage 50 Hz Frequency

Features

Audible and visual alarm	YES
Castors	NO
Integrated lock	YES
Inner lids	NO
Defrost	Manual
Battery Backup	NO
USB	NO
Data connection	NO
Digital controller with display	XR30CX
Data logging	NO
High/Low temperature alarm	YES
Porthole for external probe & CO2 backup	Ø12 mm
Prepared for external logging equipment	YES

Material

Inner Precoated white steel
Outer Galvanized pre-coated steel

Outer dimensions

Height 900 mm
Width 555 mm
Depth (incl. condenser) 580 mm
Depth (incl. condenser & handle) 630 mm
Net weight 48 kg

Inner dimensions

Height	465 mm
Width	390 mm
Depth	390 mm
Insulation	80 mm
Insulation type	PUR
Internal humidity	<5 %



Product no. N112001

Storage of	capacity				
Box height	No. of boxes	No. of racks	Total no. of boxes	Product no.	
50 mm	8	5	40	N311210	
75 mm	5	5	25	N311310	
100 mm	4	5	20	N311410	



Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

www.wolflabs.co.uk

Tel: 01759 301142

Fax: 01759 301143

sales@wolflabs.co.uk

Please contact us if this literature doesn't answer all your questions.