Chest freezer ULT C200



• Low cost of ownership

Insulation Insulation type

Internal humidity

- Limited maintenance and On-site service
- Easily installable & movable

Specifications		
Technical		
Gross volume	198 litres	
Net volume	189 litres	
Temp. range	-60°C to -86°C	
Temp. probes	1/PT 1000	
Compressor	Embraco	
Refrigerant	Nature R	
Noise level	55 dB	
Power consumption 24/h	6,0 kWh	
Power consumption	2.190 kWh/year	
Voltage	220V-240V	
Frequency	50 Hz	
Features		
Audible & visual alarm	YES	
Castors	4	
Integrated lock	4 YES	
Inner lids	2	
Defrost	2 Manual	
Battery Backup	50h	
USB	NO	
Data connection	NO	
	XR30CX	
Digital controller with display	NO	
Data logging High/Low temperature alarm	YES	
Porthole for external probe & CO:		
Prepared for external logging equ		
Contact for remote alarm	YES	
Material		
Inner	Precoated white steel	
Outer	Galvanized pre-coated steel	
Dimensions		
Height	850 mm	
Height w. castors	890 mm	
Width	920 mm	
Depth	695 mm	
Net weight	64 kg	
had a second a Para and A		
Internal dimensions	005/005	
Height	635/385 mm	
Width	550/210 mm	
Depth	440 mm	

80 mm

PUR

<5 %

- Efficient cyclopentane insulation
- Eco-friendly, HCFC-free Nature R refrigerant
- ISO 9001, 14001 & 18001 OHSAS Certified



Storage capacity					
Box height	No. of boxes	No. of racks	Total no. of boxes	Product no.	
50 mm	6 11	3 9	18 99 = 117	N311200 N311220	
75 mm	4 8	3 9	12 72 = 84	N311300 N311320	
100 mm	3 5	3 9	9 45 = 54	N311400 N311420	



Pricing on any accessories shown can be found by keying the part number into the search box on our website. The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

www.wolflabs.co.uk

Tel : 01759 301142 Fax : 01759 301143 sales@wolflabs.co.uk

Please contact us if this literature doesn't answer all your questions.