Chest freezer ULT C300



- Low cost of ownership
- Limited maintenance and on-site service
- Easily installable & movable

- Efficient cyclopentane insulation
- Eco-friendly, HCFC-free Nature R refrigerant
- ISO 9001, 14001 & 18001 OHSAS Certified

Specifications Technical Gross volume 296 litres Net volume 284 litres -60°C to -86°C Temp. range Temp. probes 1/PT 1000 Compressor Embraco Refrigerant Nature R Noise level 55 dB 7,4 kWh Power consumption 24/h Power consumption 2.701 kWh / year 220V-240V Voltage 50 Hz Frequency Features Audible & visual alarm YES 4 Castors YES Integrated lock 3 Inner lids Defrost Manual Battery Backup 50h USB NO Data connection NO Digital controller with display XR30CX NO Data logging High/Low temperature alarm YES Porthole for external probe & CO2 backup Ø12 mm YES Prepared for external logging equipment YES Contact for remote alarm

Ν	/laterial	

Inner Precoated white steel
Outer Galvanized pre-coated steel

Dimensions

Height	850 mm
Height w. castors	890 mm
Width	1260 mm
Depth	695 mm
Net weight	76 kg

Internal dimensions

Height	635/385 mm
Width	890/210 mm
Depth	440 mm
Insulation	80 mm
Insulation type	PUR
Internal humidity	<5 %



Storage capacity								
Box height	No. of boxes	No. of racks	Total no. of boxes	Product no.				
50 mm	6 11	3 18	18 198 = 216	N311200 N311220				
75 mm	4 8	3 18	12 144 = 156	N311300 N311320				
100 mm	3 5	3 18	9 90 = 99	N311400 N311420				



Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

www.wolflabs.co.uk

Tel: 01759 301142

Fax: 01759 301143

sales@wolflabs.co.uk

Please contact us if this literature doesn't answer all your questions.