Chest freezer ULT C75



- Low cost of ownership
- Limited maintenance and on-site service
- Easily installable & movable

Specifications	
Technical	
Gross volume	74 litres
Net volume	71 litres
Temp. range	-60°C to -86°C
Temp. probes	1/PT 1000
Compressor	Embraco
Refrigerant	Nature R
Noise level	53 dB
	5,10 kWh
Power consumption 24/h	
Power consumption	1.862 kWh / year
Voltage	220V-240V
Frequency	50 Hz
Features	
Audible & visual alarm	YES
Castors	4
Integrated lock	YES
Innerlids	1
Defrost	Manual
	50h
Battery Backup USB	
005	NO
Data connection	NO
Digital controller with display	XR30CX
Data logging	NO
High/Low temperature alarm	YES
Porthole for external probe & CO2 bac	okup Ø12 mm
Prepared for external logging equipmen	t YES
Contact for remote alarm	YES
Material	
Inner	Precoated white steel
Outer Ga	Ivanized pre-coated steel
Dimensions	
Height	895 mm
Height w. castors	935 mm
Width	550 mm
Depth	645 mm
Netweight	53 kg
net weight	03 KY
Internal dimensions	
Height	465 mm
Width	390 mm
Depth	390 mm
Insulation	80 mm
Insulation type	PUR
Internal humidity	<5 %

- Efficient cyclopentane insulation
- Eco-friendly, HCFC-free Nature R refrigerant
- ISO 9001, 14001 & 18001 OHSAS Certified



ctorage capacity					
Box height	No. of boxes	No. of racks	Total no. of boxes	Product no.	
50 mm	8	5	40	N311210	
75 mm	5	5	25	N311310	
100 mm	4	5	20	N311410	



Pricing on any accessories shown can be found by keying the part number into the search box on our website. The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

www.wolflabs.co.uk

Tel : 01759 301142 Fax : 01759 301143 sales@wolflabs.co.uk

Please contact us if this literature doesn't answer all your questions.