



*Digital stereomicroscope with 4 MP USB/LAN/WiFi camera, precision fixed arm, 10x - 20x - 40x, touch panel, with rechargeable battery*

<b>Observation Method - Transmitted Light</b>	Brightfield	Yes
<b>Observation Method - Incident Light</b>	Brightfield	Yes
<b>Head</b>	Type	Binocular
	Construction material	Aluminum & Plastic molds / Aluminum gears
	Inclination	45°
	Interpupillary distance (mm)	53-75
	Diopter adjustment	On both tubes
	Fixing screw for eyepieces	Yes
	Tube inner diameter (mm)	30.5
<b>Eyepieces</b>	Field number (mm)	20
	Magnification	10x
	Micrometric scale	As optional
	Diameter of micrometer glass (mm)	20
	Rubber cup	Yes
<b>Objective</b>	Optical system	Greenough
	Anti-fungus treatment	Yes
	Objective Type	Achromatic
	Working distance (mm)	60
	Standard magnifications	10x, 20x, 40x (rotating turret)
	Objective resolution	7 lp/mm @ 1x lens 19 lp/mm @ 2x lens 24 lp/mm @ 4x lens
<b>Focusing System</b>	Type	Coarse
	Coarse total travel (mm)	41
	Adjustable tension	Yes
<b>Stand</b>	Type	Precision fixed arm
	Handle	Yes
<b>Stage</b>	Frosted diffusion plate for transmitted ill.	Yes, diameter 60 mm
	Black/white contrast plate for incident ill.	Yes, diameter 60 mm
	Specimen clips	Yes
<b>Transmitted Illumination</b>	Type	LED
	Light source power (W)	1
	Brightness control	Touch Panel

	Lifetime (hours)	> 65,000
	Temperature (K)	6,300
	Max. required power (W)	1.5
<b>Incident Illumination</b>	Type	LED
	Light source power (W)	1
	Brightness control	Touch Panel
	Lifetime (hours)	> 65,000
	Temperature (K)	6,300
	Max. required power (W)	1.5
<b>Power Supply for Illumination</b>	Type	External
	Microscope connector	Jack, 2.1 mm
	Power plug type	Multi-plug (EU, UK, US)
	Input voltage	100/240 Vac, 50/60 Hz
	Output voltage	5 Vdc 500 mA
	LED indicator	Yes
	Use with batteries	Yes, not supplied
	Battery type	Ni-MH (3x, AA size), 1.2V, 1300mAh
	Working time of batteries (hours)	up to 8
	Charging time of batteries (hours)	8
<b>Accessories Included</b>	Dust cover	Yes
	Tension adjustment tool	Yes
	User Manual	Digital version (downloadable)
	USB cable (m)	1.8
	Calibration slide	Yes
<b>Additional Information</b>	Maximum sample height (mm)	35
<b>Product Dimensions</b>	Total height (mm)	288
	Base height (mm)	45
	Base width (mm)	183
	Base depth (mm)	205
<b>Product Weight</b>	(kg)	2.5
<b>Digital Head</b>	Resolution (MP)	4
	Sensor type	CMOS
	Sensor size	1/1.8"
	Sensor aspect ratio	16/9
	Full image size	2688x1512
	Pixel size (µm)	2.9x2.9
	S/N ratio (dB)	43
	Dynamic range (dB)	61
	Sensitivity (V/lux*s @550nm)	No
	Exposure time (s)	0,6 - 1/1000
	USB type	Mini USB
	System requirements	Win 7 / Win 8 / Win 10 (32/64 bit) / Win 11
	Software	ProView
	Software	LiteView
Software	Optika MobileView	
<b>USB</b>	PC Camera resolution (MP)	4
	USB standard	Mini USB
	Frame rate full resolution (fps)	30@2688*1512
<b>WiFi</b>	WiFi resolution (MP)	4
	WiFi Frame rate full resolution (fps)	30@2688*1512
	WiFi Speed	802.11ac 150Mbps
	WiFi Signal	From the camera

	WiFi Antenna	Yes
	WiFi Signal ready	About 10 seconds after turning on
	WiFi mode	AP / STA
	Max Users connected to a single camera	3
	Max number of cameras in a room (AP mode)	6
	Max number of cameras in a room (STA mode)	Not fixed. 9 cameras must be connected to a router

<b>Ethernet</b>	Ethernet resolution (MP)	4
	Ethernet type	802.3ab



# WolfLabs

**Pricing on any accessories shown can be found by keying the part number into the search box on our website.**

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

**[www.wolflabs.co.uk](http://www.wolflabs.co.uk)**

**Tel : 01759 301142**

**Fax : 01759 301143**

**[sales@wolflabs.co.uk](mailto:sales@wolflabs.co.uk)**

Please contact us if this literature doesn't answer all your questions.