



*Trinocular polarizing microscope, 600x,  
IOS N-PLAN POL objectives, transmitted  
light*

<b>Observation Method - Transmitted Light</b>	Brightfield	Yes
	Phase contrast (Positive type)	As optional
	Darkfield	As optional
	Quantitative polarized light	Yes
<b>Main Body</b>	Type	Upright
	Construction material	Aluminum die-cast
	Trasportation handle	Yes
<b>Head</b>	Type	Trinocular (Siedentopf)
	Split ratio	50/50
	Inclination	30°
	360° rotating	Yes
	Interpupillary distance (mm)	48-75
	Dioptric adjustment	On left tube
	Fixing screw for eyepieces	Yes
	Tube inner diameter (mm)	23
<b>Eyepieces</b>	Field number (mm)	20
	Magnification	10x
	Pointer	As optional
	Micrometric scale	Yes
	Diameter of micrometer glass (mm)	21
	High eyepoint (for glass wearers)	Yes
	Rubber cup	Yes
<b>Nosepiece</b>	Positions	Quadruple
	Reversed	Yes
	Bi-directional	Yes
	Rotation on ball bearings	Yes
	Objective thread	RMS
	Centerable	Yes
<b>Objectives</b>	Optical system	∞
	Anti-fungus treatment	Yes
	Parfocal distance (mm)	45
	Standard magnifications	40x-600x
	Type	IOS N-PLAN POL
		4x/0.10, W.D. 16.8 mm
		10x/0.25, W.D. 5.8 mm
	40x/0.65, W.D. 0.43 mm	
	60x/0.80, W.D. 0.14 mm	
<b>Stage</b>	Type	Round
	Rotation	360°
	Dimensions (mm)	160
	Material	Anti-scratch painting
	Specimen clips	Yes
	Slide number	1
	X-Y Vernier scale	Yes
	Vernier scale accuracy (mm)	0.1

<b>Condenser - Single Position</b>	Type	Abbe
	Removable	Yes
	Numerical aperture (N.A.)	1.25
	Magnification scale for simplified positioning	Yes
	Diaphragms	Iris
	Centrable	Yes
	Focusable	By rack and pinion
<b>Focusing System</b>	Type	Coaxial coarse & fine
	Coarse total travel (mm)	25
	Fine total travel (per single rotation) (mm)	0.2
	Fine graduations	100
	Fine resolution ( $\mu\text{m}$ )	2
	Upper stop to prevent contact	Yes
	Adjustable tension	Yes
	Flat knob for ergonomomy	Yes
<b>Transmitted Illumination</b>	Kohler illumination	Fixed (full as optional)
	Type	X-LED
	X-LED type	X-LED3
	Light source power (W)	3.6
	Brightness control	Manual
	Lifetime (hours)	> 65,000
	Temperature (K)	6,300
	Max. required power (W)	6
<b>Power Supply for Transmitted Illumination</b>	Type	External
	Microscope connector	Jack, 2.1 mm
	Power plug type	Multi-plug (EU, UK, US)
	Input voltage	100/240 Vac, 50/60 Hz
	Output voltage	6 Vdc 2.5 A
<b>Accessories Included</b>	Dust cover	Yes
	Immersion oil (10ml)	No
	Tension adjustment tool	Yes
	Allen wrench	Yes
	User Manual	Digital version (downloadable)
<b>Additional Information</b>		External rechargeable battery pack (as optional).
<b>Product Dimensions</b>	Height (mm)	460
	Width (mm)	235
	Depth (mm)	370
<b>Product Weight</b>	(kg)	7.8
<b>Polarized Light Attachment</b>	Bertrand lens - centerable	Centerable
	Bertrand lens - focusable	No
	Analyzer	90° rotatable
	$\lambda$ tint plate	Yes
	$\lambda/4$ tint plate	Yes
	Quartz wedge tint plate	Yes



# WolfLabs

**Pricing on any accessories shown can be found by keying the part number into the search box on our website.**

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

**[www.wolflabs.co.uk](http://www.wolflabs.co.uk)**

**Tel : 01759 301142**

**Fax : 01759 301143**

**[sales@wolflabs.co.uk](mailto:sales@wolflabs.co.uk)**

Please contact us if this literature doesn't answer all your questions.