

Cryostor Series

Automatic pressure regulator

Stainless Steel Construction

5 Year Vacuum Warranty

Twin fill/decant valves

Heavy Duty Castors

Electronic Indicator

Tow Bar handles

Liquid Storage

PED Compliant

Up to 3 Bar G

97/23/EC

Safe



Cryostor Series

The Cryostor Series is the latest innovation in high performance cryogenic liquid storage for the laboatory with units available from 30 to 500 litres capacity.

Stainless steel construction provides the durability to safely withstand the harshest working environments while offering lower evaporative losses when compared to traditional "liquid cylinders".





All Cryostors are equiped with a safety dispensing head incorporating fill, vent and dispense valves, safety reliefs, pressure gauge and an integral pressure build vapouriser with automatic pressure regulation.

Additionally, all units are equipped with an electronic level guage which gives an accurate reading of dewar contents at the push of a button.

Low Pressure LN2 Dewars.

For mobility, all Cryostors up to 300 litres are fitted with heavy-duty castor wheels and the larger units (180, 240 and 300 litre sizes) are equiped with a pull-along towbar handle.




Product Features

- 7 models, from 30 litres to 500 litres capacity.
- All welded stainless steel construction.
- All models equipped with heavy-duty castors up to 300 litre size.
 The 400 and 500 have a pallet truck base.
- Tow-Bar handles (180 to 300 litre models).
- Automatic pressure build circuit fitted.
- Colour-coded, labelled valves for easy identification.
- Twin liquid fill/decant valves as standard.
- Electronic contents indicator fitted.
- 5 YEAR VACUUM WARRANTY



Cryostor Head Arrangement and Technical Data



- 1. Liquid Fill/Decant
- 2. Liquid Fill/Decant
- 3. Pressure Raising
- 4. Trycock Gas Vent
- 5. Pressure Regulator
- 6. Bursting Disc
- 7. Relief Valve
- 8. Vacuum Port
- 9. Pressure Gauge
- 10. Contents Gauge

Technical Data

MODEL	Cryostor 30	Cryostor 60	Cryostor 90	Cryostor 120	Cryostor 180	Cryostor 240	Cryostor 300	Cryostor 400	Cryostor 500
PART NUMBER	9911025	9911037	9911045	9911065	9911075	9911087	9911089	9911290	9911300
Capacity (litres)	30	60	90	120	180	240	300	400	500
Evaporation Rate (%/day)	3.51	2.01	1.41	1.21	0.91	0.71	0.751	0.5	0.6
Design Code	PD:5500 CE	PD:5500 CE	PD:5500 CE	PD:5500 CE	PD:5500 CE	PD:5500 CE	PD:5500 CE	PD:5500 CE	PD:5500 CE
Weight Empty (Kg)	50	65	80	98	124	140	167	228	286
Weight Full LN2 (kg)	75	114	153	195	269	334	410	551	690
M.A.W.P.(barG)	3 ²	3²	3²	3²	3²	32	3 ²	3²	3 ²
Base Diameter (mm) Footprint dimensions	540Ø	620Ø	620Ø	720Ø	720Ø	690sq ⁴ .	814Ø	784sq ⁴ .	820sq ⁴ .
Overall Height (mm)	786³	9003	1083³	11223	13783	1645³	14393	1685³	1938³
1.2 Metre Flexible Hose Part Number	3701006	3701006	3701006	3701006	3701006	3701006	3701006	3701006	3701006
1.5 Metre Flexible Hose Part Number	3701004	3701004	3701004	3701004	3701004	3701004	3701004	3701004	3701004
Phase Seperator Part Number	9701090	9701090	9701090	9701090	9701090	9701090	9701090	9701090	9701090
1/2" BSP to CGA 295 Male to Female	1201382	1201382	1201382	1201382	1201382	1201382	1201382	1201382	1201382

1. Measured at atmospheric pressure.

2.A 1.5 BarG relief valve is fitted as standard, this can be replaced with a 3 BarG version on request.

3.Measured from floor to top of protective ring cover.

4. The Cryostor 240,400 & 500 have square bases for added stability.

5.All Cyostors are supplied with 1/2" BSPPF outlets. Alternative outlet sizes/threads are available on request.



Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

www.wolflabs.co.uk

Tel: 01759 301142

Fax: 01759 301143

sales@wolflabs.co.uk

Please contact us if this literature doesn't answer all your questions.