Variable Temperature Heat Sealer (VTS)

The VTS microplate heat sealer offers maximum flexibility without compromising on sealing quality. Stable heat sealing performance ensures one-time sealing, preventing sample loss through evaporation and cross contamination between wells.

Features:

- · Adjustable sealing temperature & time
- 125 200°C seal temperature
- Unique ergonomic design
- Stable heat sealing performance to ensure one-time sealing
- Audible indication when sealing complete
- Fast warm-up time
- Comprehensive range of heat sealing foils & films available (see page 7)









The VTS requires at least ONE adaptor plate. Adaptors sold separately.

V902003 VTS Adaptor: Microtitre Plates (skirted)

V902004 VTS Adaptor: 96 Well Plates (semi-skirted/unskirted)

V902005 VTS Adaptor: Deep Well Plates



Microplates

Microplates are suitable for micro-volume applications such as sample and reagent transfer and storage; ensuring maximum sample recovery when limited sample material is available. Transparent polypropylene provides improved sample visibility, with alphanumeric coding making it easier to identify individual wells and reduce the risk of errors. For best results, use with the VTS and MicroTS heat sealers.



Features:

- Excellent chemical compatibility
- Temperature Range -80°C to 121°C
- Standard footprint 128mm x 86mm
- Easy-to-read alphanumeric label
- Polypropylene (PP)

Catalogue Number	Quantity	Skirt	Sterile	Well Count	Well Volume
V801001	100	1	Х	96	0.2ml
V801002	10	1	Х	96	0.2ml
V801003	10	1	1	96	0.2ml
V801004	100	Х	Х	96	0.2ml
V801005	10	Х	Х	96	0.2ml
V801006	10	Х	1	96	0.2ml
V801007	100	1	Х	384	25ul
V801008	10	1	Х	384	25ul
V801009	10	1	1	384	25ul
V801013	50	1	Х	96	1.3ml
V801014	10	/	Х	96	1.3ml
V801015	10	1	1	96	1.3ml
V801016	50	1	Х	96	2.2ml
V801017	10	1	Х	96	2.2ml
V801018	10	/	1	96	2.2ml








Heat Sealing Foils & Films

Our comprehensive range of foil and film microplate heat seals are designed for sealing various plate formats; providing optimum protection against sample loss through evaporation making them ideal for long-term storage. For best results use Vitl heat seals in conjunction with the VTS and MicroTS heat sealers.



Features:

- · Colour coded for easy identification
- 125mm x 80mm sheets
- All foils & films available in standard packs of 100 sheets
- Custom reels of seals for automated heat sealers are available on request
- Range of seal thicknesses & formats including optically clear, peelable, pierceable & DMSO resistant
- · 'This side up' markings to avoid incorrect sealing

Applications:

- Sample Storage
- Sample Archiving
- PCR



Heat Sealing Foils & Films	Sealir	Po Foi	S S S	-ilms					
Product	Peelable	Piercable	Temp Range	Polyethylene Plate (PP)	Polypropylene Plate (PE)	Polystyrene Plate (PS)	COC?	Colour	Catalogue Number
20µm Heat Sealing Foil	×	>	-20 - +120°C	`	<i>,</i>	`	×	Green	V901002
38µm Heat Sealing Foil	`	>	-20- +110°C	`	`	`	×	Blue	V901003
68µm Heat Sealing Foil	`	×	-80- +110°C	`	`	`	>	Yellow	7901008
70µm Heat Sealing Foil	`	>	-80 - +80°C	`	`	`	>	Orange	V901010
70µm Heat Sealing Foil	`	×	-80 - +80°C	`	`	×	×	Red	1001067
75µm Clear Sealing Film	×	>	-80 - +80°C	>	<i>></i>	>	>	75µm	7901005
85µm Heat Sealing Foil	`	×	-200- +110°C	`	×	×	×	Black	V901004
105µm Clear Sealing Film	>	×	-80 - +180°C	`	`	`	>	105µm	7901006

V901020 Foil Weight (sold separately)

Not sure which heat seal is right for you? Contact us for a free sample pack





Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

www.wolflabs.co.uk

Tel: 01759 301142

Fax: 01759 301143

sales@wolflabs.co.uk

Please contact us if this literature doesn't answer all your questions.