



## 250kg flake ice machine with 280kg slope fronted bin

The Ziegla ZBE250-S280 ice machine makes up to 250kg of flake ice in one of two sizes. It sits on an S280 slope fronted ice storage bin, which stores 280kg of ice ready for use. The ice machine has a B type ice discharge / level control, which drops ice into the bin below, stops ice production when the bin is full and automatically restarts once ice is removed.



### ZBE250 main features

- Ice level control system included as standard
- Granular flake ice made at optimum temperature of  $-0.5^{\circ}\text{C}$ .
- Two sizes of ice flake available: micro and midi, to suit a wide range of applications
- Hygienic design with a sealed water system
- External water filtration system supplied as standard.
- Designed for continuous operation 24/7
- Stainless steel construction
- No moving parts in refrigeration circuit lowers risk of gas leaks
- Environmentally friendly natural refrigerant



**Enquire about this  
Machine now**

### S280 ice storage features

Stainless steel construction

Poly lined interior for easy cleaning and maximum chlorine resistance.

Non CFC insulation

Model	<b>ZBE 250-S280</b>
250kg / 24h nominal capacity*	at 20°C air and 15°C water
Ice storage capacity	280kg (0.85m³)
Assembled dimensions (W x D x H)	1220 x 807 x 1875 mm
Assembled weight (empty)	185kg
cabinet	Stainless steel 1.4301
<b>Electricity</b>	
power consumption	0.8kW
current consumption	3.6A
<b>Provided by customer</b>	
electric supply	1/N/PE ~ 230V 50Hz
fuse, slow-blow	16A
cable cross section, Cu	1.5mm²
<b>Water</b>	
supply / drain	¾" BSP / 18mm O/D hose (floor drain recommended)
<b>provided by customer</b>	
pressure	2 – 5 bar
quality	drinking water quality
pH value	7.2 – 9.5 pH
hardness	6 – 14 °dH
	100 – 250mg CaCO₃/l
temperature	5°C - 30°C
Ambient air temperature	5°C - 42°C

Condenser	Air cooled
air flow	440 m3/h
heat emission	2.0kW

Refrigerant R290	0.112kg
ODP	0
GWP	3

Compressor	Fully hermetic
refrigeration capacity	1.2kW
evaporation temperature	-14°C
condensation temperature	33°C

Noise level	51dBA (3m)
-------------	------------

Ice discharge	B type
---------------	--------

Shipping dimensions (W x D x H)	(0.76 x 0.66 x 0.79m) + (1.4 x 0.9 x 1.28m)
---------------------------------	---

Shipping weight	(95kg) + (105kg)
-----------------	------------------

\*according to site conditions. Air temperature, water temperature, water chemistry, air contamination and installation parameters can all effect ice output.



# WolfLabs

**Pricing on any accessories shown can be found by keying the part number into the search box on our website.**

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

**[www.wolflabs.co.uk](http://www.wolflabs.co.uk)**

**Tel : 01759 301142**

**Fax : 01759 301143**

**[sales@wolflabs.co.uk](mailto:sales@wolflabs.co.uk)**

Please contact us if this literature doesn't answer all your questions.