

Thermo Mix

HCM100-Pro/HM100-Pro

Thermo Mix series integrates precise and efficient heating & cooling and mixing function

DLAB HCM100-Pro-Heating/Cooling/Mixing

DLAB HCM100-Pro combines the excellent mixing and accurate temperature control, to make your work efficiently and productively



Features

- Fully programmable
- Precise temperature control for heating and cooling
- Real-time display of speed, temperature and time
- Excellent mixing (200-1500rpm)
- Quick interchange of blocks without tools and automatic block recognition
- Compatible with most popular tubes
- Block equipped with a lid for heat preservation
- Temperature self-calibration

Applications

Precise and efficient heating/cooling and mixing is applicable for many applications such as Gene synthesis, gene purification, gene and protein denaturation, enzymatic reaction, bacterial growth, and others.

Thermo Control

HC110-Pro

heating and cooling with digital display



Features

- Compact, programmable and overheating protection for safe sample handling
- Precise temperature control for heating and cooling -5°C to 110°C for all major lab applications
- Interchangeable sample blocks available
- Most common application includes reagent warming/cooling, DNA extractions, enzymatic reactions and reactions that need to be processed at or near room temperature.

As low as -5°C

Precise temperature control for heating and cooling between -5°C-110°C.

Specifications	HCM100-Pro	HM100-Pro	HC110-Pro
Functions	Heating,cooling&mixing	Heating&mixing	Heating&cooling
Temperature range [°C]	Below room temp 15- 100	Room temp-100	Below room temp 25- 110
Temperature Setting range [°C]	0-100	0-100	-5-110
Temperature control accuracy@20-45 [°C]	±0.5	±0.5	±0.5
Temperature uniformity@20-45 [°C]	±0.5	±0.5	±0.5
Power [W]	200	200	200
Time setting range	0min~99h30min	0min~99h30min	0min~99h30min
Max Heating speed	5.5°C/min	5.5°C/min	5.5°C/min
Max Cooling speed	5°C/min (100°C-room temp) 0.5°C/min (below room temp)	-	2.5°C/min (100°C-room temp) 0.5°C/min (below room temp)
Mixing speed [rpm]	200-1500	200-1500	-
Mixing orbit [mm]	3	3	-
Display	TFT	TFT	TFT
Program	9	9	9
Overheating protection [°C]	150	150	150
Voltage,Frequency	110/220V, 50/60HZ	110/220V, 50/60HZ	110/220V, 50/60HZ
Dimension [mm]	200x235X120	200x235X120	200x235X120
Weight [kg]	7.3	7.3	7.3
Operating temperature [°C]	10-40	10-40	10-40
Operating humidity [% RH]	<80	<80	<80

Blocks

H100-Pro/HC110-Pro/HCM100-Pro/HM100-Pro

Cat.No	Magnetic	18900401	18900402	18900403	18900404	18900405	
	Mechanical fixation	18900344	18900343	18900345	18900637	18900638	
Block types							
Capacity	0.5mL×24	1.5mL×24	2mL×24	5mL×8 round bottom	5mL×8 cone bottom		
Speed	1500rpm	1500rpm	1500rpm	1500rpm	1400rpm		
Diameter×depth	8.1×26mm	10.9×30.8mm	10.9×30.8mm	13.6×42mm	17×51.5mm		
Cat.No	Magnetic	18900874	18900406	18900407	18900420	18900423	18900746
	Mechanical fixation	—	18900241	18900242	18900349	18900350	—
Block types							
Capacity	1.5mL×24 Chromatography Vial	15mL×8	50mL×4	0.2mL×8 PCR strips or 0.2mL×96 PCR microplate		ELISA microplate	Deep well Plate
Speed	1500rpm	800rpm	600rpm	1500rpm		1500rpm	—
Diameter×depth	12×20.5mm	16.9×80mm	29.6×80mm	5.7×13.2mm		127×85mm	127×85×42mm

HB120-S/HB120-SC (Standard:151×95×50mm, Thin:151×95×36.5mm)

Cat.No	Standard	18900218	18900219	18900253	18900220	18900818	18900221	
	Thin	18900274	18900275	18900276	18900277	18900877	—	
Block types								
Capacity	0.2mL×54	0.5mL×40	1.5mL×40	2mL×40	2mL×60 Ampoules tubes		5/15mL×28	
Diameter×depth	6.4×15mm	8.2×26.4mm	11×34.7mm	11×34.7mm	12×37mm	17×48mm		
Cat.No	Standard	18900222	18900224	18900223	18900546		—	
	Thin	—	18900278	18900279	—		18900504	
Block types								
Capacity	50mL×8	0.2mL+0.5mL +1.5/2mL 18+18+18	microplate	5mL blood collection tubex45		0.2mL×8 PCR strips or 0.2mL×96 PCR microplate		
Diameter×depth	29.8×48mm	Each capacity	127×85mm	13.5×48mm		5.7×13.2mm		
Capacity	Cat. No.18900523			Capacity				
Two-in-one block, bead bath/water bath Adapt to S2			Aluminum beads					
								



WolfLabs

Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

www.wolflabs.co.uk

Tel : 01759 301142

Fax : 01759 301143

sales@wolflabs.co.uk

Please contact us if this literature doesn't answer all your questions.