

Miniature Shaker KM CO2-FL



Description

The shaker KM CO2 made of stainless steel was especially designed for use in incubators with up to 20% CO2 concentration and up to 95% humidity. This guarantees the optimum development of your cell cultures.

Because of the ribbon cable a feedthrough is not required in the incubator.

Basic Equipment

Basic device incl. basic platform with rubber mat and external control unit with ribbon cable

Loading Capacity

Erlenmeyer flasks 100 ml 9 pieces

Erlenmeyer flasks 500 ml 2 pieces

You will find further loading possibilities [here](#)

Details

Motion:	orbital
Shaking platform:	200 x 295 mm
Max. load:	2 kg
Shaking speed:	5 - 220 rpm, in steps of 5

Stroke: 20 mm
Runtime: 1s - 100 h / continuous
Order No.: 6137 000
Accessory: Universal tray KM Mini
Universal tray KM
Clamping strip KM

Technical specifications

Electrical supply: 100 - 240 V, 50 / 60 Hz
Enclosure protection: IP 21
Heat emission: approx. 4 W
Ambient temperature: 4°C to 45°C
Relative humidity: 20 - 95 %
CO2 concentration: 20 %
Dimensions (w x d x h): 230 x 340 x 145 mm
Weight: 7,6 kg



WolfLabs

Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

www.wolflabs.co.uk

Tel : 01759 301142

Fax : 01759 301143

sales@wolflabs.co.uk

Please contact us if this literature doesn't answer all your questions.