Key Features 6305

- Wavelength range of 198 to 1000nm
- Xenon lamp
- Easy and intuitive operation
- Absorbance, %T and concentration modes
- Multi-parameter display with wavelength and photometric readouts
- Wide range of sampling accessories
- 3 year warranty



UV/Visible Spectrophotometer

The 6305 is ideal for applications similar to the 6300 requiring measurements in the UV and visible wavelength ranges. Using a single, pulsed xenon lamp the 6305 offers an extended lamp life and high energy throughput in the UV and visible regions.

Technical Specification

Wavelength

Range 198 to 1000nm

Resolution 1nm Accuracy ±2nm

Spectral bandwidth 8nm, 6nm over UV range

Photometrics

Transmittance 0 to 199.9%T
Absorbance -0.300 to 1.999A

Accuracy ±1%T

Resolution 0.1%T, 0.001A

Stray light <0.5%T at 220 and 340nm Noise <0.001A at 0A at 400nm Stability <0.002A/h after 30 minutes

Concentration

Range -300 to 1999
Resolution 0.1 to 1

Units ppm, mg/l, g/l, M, %, blank Factor 0 to 199.9, 1000 to 9999

Other

Light source Xenon lamp

Outputs Analogue and RS232

Power <50W*

Size (w x d x h), mm 365 x 272 x 160

Weight, kg 6

Ordering Information

Part Code Description 635 001 6305 UV/Visible spectrophotometer supplied with mains lead, pack 100 disposable cuvettes, 10x10mm cell holder, interface cable and 63-Zero PC application software on CD-ROM** (230/50Hz)

- * Voltage variants available see page 94
- ** Requires free on-line registration



Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

www.wolflabs.co.uk

Tel: 01759 301142

Fax: 01759 301143

sales@wolflabs.co.uk

Please contact us if this literature doesn't answer all your questions.