

Features

- 100% oil free
- 100% duty cycle
- compact and easy to use
- easy maintenance
- long-life, 2-year warranty
- 8000 hours cup life at 8bar
- 4000 hours maintenance interval for the dryer

OTHER VERSIONS

- without dryer (2xOF302-40B)
- with soundproofing cabinet (2xOF302-40MQ2)

Description

• built-in 2-column adsorption dryer

JUN-AIR


- pressure dew point down to -40°C
- 1µm air filtration (class 2 for dust according to ISO8573.1:2001)
- pressure regulator included
- receiver with internal coating and 5-year warranty

Model 2xOF302-40BQ2 Voltage ٧ 1x230 1x120 Frequency Hz 50 60 Motor HP 1.2 1.2 kW 0.9 0.9 Displacement 216 276 l/min 70 Air flow @ 8bar l/min 60 cfm 2.12 2.5 Max. pressure bar 8 8 120 120 psi Max. current 6.8 13.2 А **Receiver volume** litres 40 40 gallon 10.6 10.6 Weight 59 59 kg 130 130 lbs Noise level dB(A)/1m 68 68 100% Duty cycle 100%

Air flow / pressure curve ¹⁾


Product

specifications



1) air flow is reduced by 18 to 20% on units with dryers

Dimensions - inches / [mm]²⁾



2) for unit without accessories or options



Pricing on any accessories shown can be found by keying the part number into the search box on our website. The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

www.wolflabs.co.uk

Tel : 01759 301142 Fax : 01759 301143 sales@wolflabs.co.uk

Please contact us if this literature doesn't answer all your questions.