


OFI 202-40B (oil-less)

Voltage	V	200	200	230	240	3x400	3x440					
Frequency	Hz	50	60	50	60	50	60					
Motor	HP	2.00	2.00	2.00	2.00	2.00	2.00					
	kW	1.47	1.47	1.47	1.47	1.47	1.47					
Displacement	l/min	290	328	290	328	290	328					
	CFM	10.24	11.58	10.24	11.58	10.24	11.58					
FAD @ 8 bar	l/min	130	146	130	146	130	146					
	CFM	4.59	5.16	4.59	5.16	4.59	5.16					
Max. pressure ¹⁾	bar	8	8	8	8	8	8					
	psi	120	120	120	120	120	120					
Max. current	A	-	-	8.0	9.0	5.0	5.0					
Tank size	litres	40	40	40	40	40	40					
	gallon	10.6	10.6	10.6	10.6	10.6	10.6					
Weight	kg	59	59	59	59	59	59					
	lbs	130	130	130	130	130	130					
Noise level	dB(A)/1m	76	79	76	79	76	79					
Thermal protection		Yes	Yes	Yes	Yes	Yes	Yes					
Duty cycle		100%	100%	100%	100%	100%	100%					



Dimensions (l x w x h)
556 x 442 x 677 mm / 21 7/8 x 17 3/8 x 26 5/8 inch

¹⁾ Higher pressure available upon request

Technical modifications reserved

JUN-AIR®





WolfLabs

Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

www.wolflabs.co.uk

Tel : 01759 301142

Fax : 01759 301143

sales@wolflabs.co.uk

Please contact us if this literature doesn't answer all your questions.