


24-40 (oil-lubricated)

Voltage	V	200	200	230	230	3x200	3x200	3x208	3x400 ²⁾	3x440 ²⁾		
Frequency	Hz	50	60	50	60	50	60	60	50	60		
Motor	HP	1.84	1.84	1.84	1.84	1.84	1.84	1.84	1.84	1.84		
	kW	1.35	1.35	1.35	1.35	1.35	1.35	1.35	1.35	1.35		
Displacement	l/min	200	240	200	240	200	240	240	200	240		
	CFM	7.06	8.48	7.06	8.48	7.06	8.48	8.48	7.06	8.48		
FAD @ 8 bar	l/min	128	148	128	148	128	148	148	128	148		
	CFM	4.52	5.23	4.52	5.23	4.52	5.23	5.23	4.52	5.23		
Max. pressure ¹⁾	bar	8	8	8	8	8	8	8	8	8		
	psi	120	120	120	120	120	120	120	120	120		
Max. current	A	11.6	11.6	11.6	11.6	8.7	8.7	8.7	5.8	5.8		
Tank size	litres	40	40	40	40	40	40	40	40	40		
	gallon	10.6	10.6	10.6	10.6	10.6	10.6	10.6	10.6	10.6		
Weight	kg	84	84	84	84	84	84	84	84	84		
	lbs	185	185	185	185	185	185	185	185	185		
Noise level	dB(A)/1m	56	56	56	56	56	56	56	56	56		
Thermal protection		Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes		
Duty cycle		50%	50%	50%	50%	50%	50%	50%	50%	50%		



Dimensions (l x w x h)
590 x 540 x 610 mm / 23 2/8 x 21 1/8 x 24 inch

¹⁾ Higher pressure available upon request

²⁾ Neutral is required

Technical modifications reserved

JUN-AIR®





WolfLabs

Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

www.wolflabs.co.uk

Tel : 01759 301142

Fax : 01759 301143

sales@wolflabs.co.uk

Please contact us if this literature doesn't answer all your questions.