

KERN OBN 142

The fluorescence microscope for the professional user

KERN



Category

Brand	Optics
Product category	Microscope
Product group	Fluorescence microscope
Product family	OBN-14

Construction

Dimension (W×D×H)	530×220×490 mm
Optical system	Infinity
Tube type	Trinocular
Tube angle of inclination	30°
Tube 360° rotation	✓
Tube type	Siedentopf
Light distribution	100:0

Contrasting methods

Bright field
Darkfield (optional)
Fluorescent
Polarisation (optional)
Phase contrast (optional)

Standard objectives

4×
10×
20×
40×
100×

Lens quality Infinity Plan

Nosepiece screw-in locations	5
Interpupillary distance [Min]	50 mm
Interpupillary distance [Max]	75 mm
Diopter adjustment	both-sided
Diopter adjustment [Min]	-5
Diopter adjustment [Max]	5
Colour temperature	6000 K

Ocular

Ocular type	Eyepiece HWF 10 x / Ø 20mm with anti-fungus, high eye point
Ocular field width	HWF
Ocular magnifications	10 x
Ocular visual field	20 mm
Ocular diameter	23,2 mm

Objective

Objectives - Details	Objective Infinity Plan 10 x / 0,25 anti-fungus Objective Infinity Plan 100 x / 1,25 oil, spring, anti-fungus Objective Infinity Plan 20 x / 0,4 spring, anti-fungus Objective Infinity Plan 4 x / 0,11 anti-fungus Objective Infinity Plan 40 x / 0,66 spring, anti-fungus
Objectives magnifications	4 x / 10 x / 20 x / 40 x / 100 x

Illumination

Illuminance	Reflected light Transmitted light
Illumination type incident light	LED
Illumination type transmitted light	LED
Illumination intensity incident light	5 W
Illumination intensity transmitted light	3 W
Illumination dimmable	Incident light + Transmitted light, separate
Koehler illumination	✓
Filter possible	✓
Field diaphragm	✓

Focussing

Field of view [Min]	0,2 mm
Field of view [Max]	5 mm
Torque regulation	✓
Fine drive minimum	0,002 mm
Focusing mechanism	coaxial coarse and fine drive

KERN OBN 142



The fluorescence microscope for the professional user

Power Supply

Supplied power supply	Power supply unit
Plug-in power supply type	Power adapter
Input voltage power supply / power [Max]	100 V - 240 V AC 50/60 Hz 0,3 A
Input voltage device / power [Max]	5 V, 1 A

Environmental conditions

Storage temperature [Min]	-5 °C
Storage temperature [Max]	40 °C

Approval

CE mark	✓
---------	---

Packing & Shipping

Delivery time	1 d
Dimensions packaging (W×D×H)	510×470×500 mm
Shipping method	Parcel service
Net weight approx.	13 kg
Gross weight approx.	16 kg
Shipping weight	24 kg

Pictograms

STANDARD



OPTION





WolfLabs

Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

www.wolflabs.co.uk

Tel : 01759 301142

Fax : 01759 301143

sales@wolflabs.co.uk

Please contact us if this literature doesn't answer all your questions.