

Stereo microscope sets KERN OZM-9



Predefined stereo microscope sets with PREMIUM universal stand and illumination for your functional workplace

OZM 952/953

Features

- Sets which have already been defined, consisting of a stereo microscope head (p. 74), a universal stand (p. 79/80), a holder (p. 81), a ring illumination (p. 83) and a dust cover (p. 81) from our range
- Simple convenient affordable
- This saves you spending time on configuration and being spoilt for choice in the combination of different components. In this way you get an in expensive and highly-flexible solution for your microscope workplace

OZM 982/983

Model	Microscope head		Stand	Holder	Illumination
KERN	Tube	Objective Zoom			
OZM 912	Binocular (OZM 546)	0,7×-4,5×	Telescopic arm with plate (OZB-A5201)	With coarse focusing knob Adjustable torque of the hand wheels (OZB-A5301)	4,5 W LED ring light (OBB-A6102)
OZM 913	Trinocular (OZM 547)	0,7×-4,5×	Telescopic arm with plate (OZB-A5201)	With coarse focusing knob Adjustable torque of the hand wheels (OZB-A5301)	4,5 W LED ring light (OBB-A6102)
OZM 932	Binocular (OZM 546)	0,7×-4,5×	ball-beared double telescopic arm with plate (OZB-A5203)	With coarse focusing knob Adjustable torque of the hand wheels (OZB-A5301)	4,5 W LED ring light (OBB-A6102)
OZM 933	Trinocular (OZM 547)	0,7×-4,5×	ball-beared double telescopic arm with plate (OZB-A5203)	With coarse focusing knob Adjustable torque of the hand wheels (OZB-A5301)	4,5 W LED ring light (OBB-A6102)
OZM 952	Binocular (OZM 546)	0,7×-4,5×	Jointed arm with clamp (OZB-A5212)	With coarse focusing knob Adjustable torque of the hand wheels (OZB-A5301)	4,5 W LED ring light (OBB-A6102)
OZM 953	Trinocular (OZM 547)	0,7×-4,5×	Jointed arm with clamp (OZB-A5212)	With coarse focusing knob Adjustable torque of the hand wheels (OZB-A5301)	4,5 W LED ring light (OBB-A6102)
OZM 982	Binocular (OZM 546)	0,7×-4,5×	Spring loaded arm with clamp (OZB-A6302)	With coarse focusing knob Adjustable torque of the hand wheels	4,5 W LED ring light (OBB-A6102)
OZM 983	Trinocular (OZM 547)	0,7×-4,5×	Spring loaded arm with clamp (OZB-A6302)	With coarse focusing knob Adjustable torque of the hand wheels	4,5 W LED ring light (OBB-A6102)



Pictograms



360° rotatable





Monocular Microscope

For the inspection with one eye



Binocular Microscope

For the inspection with both eyes



Trinocular Microscope

For the inspection with both eyes and the additional option for the connection of a camera



Abbe Condenser

With high numerical aperture for the concentration and the focusing of light



Halogen illumination

For pictures bright and rich in contrast



LED illumination

Cold, energy-saving and especially long-life illumination



Incident illumination

For non-transparent objects



Transmitting illumination

For transparent objects



Fluorescence illumination

For stereomicroscopes



FPS


Fluorescence illumination

for compound microscopes With 100W mercury lamp and filter



Fluorescence illumination for compound microscopes

With 3 W LED illumination and filter



Phase contrast unit



Darkfield condenser/unit

For a higher contrast due to indirect illumination



Polarising unit

To polarise the light



Infinity system

Infinity corrected optical system



Zoom magnification For stereomicroscopes

Auto-focus

For automatic control of the focus level



Parallel optical system

For stereomicroscopes, enables fatigue-proof working



Integrated scale

In the eyepiece



SD card

For data storage



USB 2.0 digital camera



For direct transmitting of the picture to a PC



USB 3.0 digital camera

For direct transmitting of the picture to a PC



WLAN data interface

For transmitting of the picture to a mobile display device



HDMI digital camera

For direct transmitting of the picture to a display



PC software

To transfer the measurements from the device to a PC



Automatic temperature compesation

For measurements between 10 °C and 30 °C



Protection against dust and water splashes

IPxx: The type of protection is shown in the pictogram cf. DIN EN 60529:2000-09, IEC 60529:1989+A1:1999+A2:2013



Battery operation

Ready for battery operation. The battery type is specified for each device.



Battery operation rechargeable

Prepared for a rechargeable battery operation



Plug-in power supply

230V/50Hz in standard version for EU. On request GB, AUS or USA version.



Integrated power supply unit

Integrated in microscope. 230V/50Hz standard EU. More standards e.g. GB, AUS or USA on request.



Package shipment

The time required to manufacture the product internally is shown in days in the pictogram.

Abbreviations

Adapter for the connection of a C-Mount

Frames per second

camera to a trinocular microscope

LWD Long Working Distance SWF Super Wide Field (Field number at least Ø 23 mm for 10× eyepiece)

N.A. Numerical Aperture

Working Distance W.D.

H(S)WF High (Super) Wide Field (Eyepiece with high eye point for wearers of glasses)

SLR camera

Single-Lens Reflex camera

WF Wide Field (Field number up to

Ø 22 mm for 10× eyepiece)

Your KERN specialist dealer:



Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

www.wolflabs.co.uk

Tel: 01759 301142

Fax: 01759 301143

sales@wolflabs.co.uk

Please contact us if this literature doesn't answer all your questions.