

Standing: 2025-08-27

LAUDA Universa U 855 M

Cooling thermostat, 200-240 V; 50/60 Hz

Part Number: L003805

#### **Features**

- · Bath circulation thermostat with advanced electronics ensures precise control accuracy
- Future-proof thanks to modularity: LAUDA Universa with interchangeable control head and heating/cooling base allows flexible adaptation to current and future requirements.
- Clear overview, intuitive operation: The 5-inch colour TFT display simultaneously shows temperature values with a progression graph, offers clear menu navigation in six languages and clear operating status icons easily controlled via cursor and soft keys.
- Focus on safety: The dedicated Tmax button provides convenient access to the essential overtemperature protection setting during commissioning.
- Versatile pressure-suction pump: The LAUDA Varioflex pump, a powerful pressuresuction pump, offers eight selectable performance levels, adjustable flow rate distribution for internal/external circulation for optimal volume flow and pressure
- Easily accessible front switch on the control head allows the pump output to be adjusted during operation.
- Highly efficient refrigeration technology: Combination of speed-controlled inverter
  compressor and capacity control by means of electronic expansion valves and speed-controlled fans for improved energy
  efficiency and reduced operating costs, increased service life by avoiding frequent switch-on and switch-off cycles, dynamic approach to the set temperature and quieter operation.
- · Environmentally friendly refrigerants: Use of natural refrigerants for sustainable and environmentally conscious cooling.
- Adaptive bath edge ventilation (patent application): Prevents icing and condensation Stops water entering the bath -Blocks vapors to protect electronics. To increase operational safety and extend service life.
- Extensive functionality with programmer, safe mode, calibration options, controller self-adaptation and weekly planner for precise and flexible process control.
- Intelligent remote control and monitoring: Integrated web server allows flexible remote control in the company network via the LAUDA Command app or browser-based, secured by PKI and 2-factor authentication. The connection to LAUDA.LIVE enables global, cloud-based data analysis and remote maintenance.
- Maximum networking: Comprehensive connectivity for almost any application thanks to standard Ethernet, USB and interface for an external Pt100 as well as eleven optional interface modules.
- Wireless communication: Integrated WLAN enables effortless connection with PC, tablet and smartphone.



# serve technical change:



### PRODUCT DATA SHEET

Standing: 2025-08-27

LAUDA Universa U 855 M

Cooling thermostat, 200-240 V; 50/60 Hz

Part Number: L003805

#### **Features**

• Comprehensive safety functions: - Effective over- and under-level protection - Adjustable overtemperature protection with acoustic alarm - Automatic system diagnostics at start-up with alarm and error message display - Smart temperature control media management with automatic limit value adjustment. For reliable operation and improved safety of your valuable samples.



Working temperature min.

-55 °C



Working temperature max.

200°C

## eserve technical change



## PRODUCT DATA SHEET

Standing: 2025-08-27

LAUDA Universa U 855 M

Cooling thermostat, 200-240 V; 50/60 Hz

Part Number: L003805

#### Technical Features

Working temperature range
Operating temperature range
Ambient temperature range
Temperature stability
Heating capacity range
Current max.
Size of bath $(W \times D \times H)$
Bath opening (WxT)
Bath volume min. / max.
Pump Pressure max.
Pump suction max.
Pump flow rate max. (pressure)
Pump Flow rate max. (suction)
In / Outlet connection thread (outside)
In / Outlet Ø olives
Overall dimensions (WxDxH)
Weight
Refrigerant stage 1
Power supply
Power plug

-55 200 °C
-55 200 °C
540°C
0.01 ± K
2.6 3.1 kW
13 A
150 x 150 x 200 mm
150 x 150 mm
5.0 / 8.0 L
0,7 bar
0,4 bar
25 L/min
23 L/min
M16 x 1
13 mm
310 x 490 x 757 mm
45 kg
R-1270 (GWP 3); 0.075 kg; 0.0 t CO2-eq
200-240 V, 50/60 Hz
Power cord with angled plug (BS1363)



Power cord with angled plug (BS1363)



Standing: 2025-08-27

LAUDA Universa U 855 M

Cooling thermostat, 200-240 V; 50/60 Hz

Part Number: L003805

Temperature	Pump stage	Heat transfer liquid	Cooling Capacity 50 Hz	Cooling Capacity 60 Hz
200 °C	8	Thermal oil	1.6 kW	1.6 kW
100 °C	8	Thermal oil	1.6 kW	1.6 kW
20 °C	8	Ethanol	1.6 kW	1.6 kW
10 °C	8	Ethanol	1.45 kW	1.45 kW
0 °C	8	Ethanol	1.25 kW	1.25 kW
-10 °C	8	Ethanol	0.88 kW	0.88 kW
-20 °C	4	Ethanol	0.62 kW	0.62 kW
-30 °C	4	Ethanol	0.38 kW	0.38 kW
-40 °C	4	Ethanol	0.18 kW	0.18 kW
-50 °C	4	Ethanol	0.05 kW	0.05 kW
-55 °C	4	Ethanol	0.02 kW	0.02 kW

#### Standard accessories

- 1 Bath cover
- Pump connection set with M16x1 stainless steel connections
- · 2 screw caps, 2 closing plugs
- 2 nipples 13 mm for pump connectors

Reserve technical changes




Standing: 2025-08-27

LAUDA Universa U 855 M

Cooling thermostat, 200-240 V; 50/60 Hz

Part Number: L003805






Standing: 2025-08-27

LAUDA Universa U 855 M

Cooling thermostat, 200-240 V; 50/60 Hz

Part Number: L003805





Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

## www.wolflabs.co.uk

Tel: 01759 301142

Fax: 01759 301143

sales@wolflabs.co.uk

Please contact us if this literature doesn't answer all your questions.