# Pharmacy Plus Bluetooth Enabled Refrigerator

# 310L Pharmacy Plus Upright Fridge with Glass Door with Digital Lock

GDMAcode PPGR310BT-DLK

SKU code 444411392







#### Key features

- ✓ Local monitoring and alarm history via Bluetooth
- ✓ Power failure alarm with backup battery powered recording
- √ Solid and glass door options
- ✓ Intelligent fan management system for enhanced performance











#### Bluetooth Connected Controller

Local temperature monitoring and alarm history via Bluetooth connectivity. Power failure alarm with battery back-up, providing continuous temperature monitoring in the event of power outage.

# Lec Medical Smartphone App

Contactless local monitoring of air and load temperatures via smart phone app. Downloadable temperature report and alarm history.

# Intelligent Fan Management

Smart fan optimisation aides in temperature stability following door openings, minimising fan activity when door is open to reduce the rate of temperature increase.

## Dual Probe Temperature Monitoring

Our dual probe system offers greater temperature accuracy within your appliance, simultaneously measuring both air and product temperatures.

## Flexible Internal Storage

Multiple shelf locations provides flexible storage solutions.



### Specification: 310L Pharmacy Plus Upright Fridge with Glass Door and Digital Lock

Gross Capacity (litres)	310L
Net Capacity (litres)	305L
Unit External Width (mm)	595mm
Unit External Depth (mm)	660mm
Unit External Height (mm)	1560mm
Product Weight (kg)	50.0Kg
Packed Width (mm)	640mm
Packed Depth (mm)	660mm
Packed Height (mm)	1560mm
Packed Weight (kg)	57Kg
Country of Origin	UK
Internal Dimensions (mm) (WxDxH) Temperature Range	515mm x 480mm x 1415mm +2°C to +8°C
Colour	White/green
External Finish	Painted Steel
Internal Finish	HIPS*
Type of plastic	SRL800 (HIPS/ABS mix)
Door Finish	Painted Steel / Solid
Door Type	Glass
Door Style	Hinged, right handed only, Non-reversible
Door Liner	Flat
Number of Door Trays	n/a
Number of Door Tray Positions	n/a
Door Open Depth (mm)	1150mm
Replacement Door Seal	Yes
Open Door Sensor	Yes
Lock	Yes, 2 Keys
Adjustable Feet (number & position)  Porthole	2 adjustable (front)
Porthole Size	Yes 16 mm
Porthole Location	Rear Bottom
Temperature Display on Panel	Yes
Temperature Alarm	Yes
Remote Alarm Contacts	Yes
Audible Alarms	Yes
Visual Alarms	Yes
Number of Shelves/Drawers	5
Number of Shelf Positions	9
Shelf Size (mm) (WxDxH)	496mm x 405mm x 6mm
Shelf Material	Polythene Coated Wire
Drawer Size (mm) (WxDxH)	n/a
Drawer Material	n/a
Number of Baskets	Dob those Costed Mixe
Basket Material Basket Size (mm) (WxDxH)	Polythene Coated Wire 485mm x 255mm x 171mm
Interior Light	40311111 X 23311111 X 171111111 Yes
Light Type	LED
Light Activation	Door Switch / Controller
Fan	Yes - Tangential
Spark Free	No
Defrost setting	Auto (Off Cycle)
Controller Type	Digital BT, External
Battery Back Up/Hours	No
Bluetooth	Yes
NFC	Yes
WIFI Number of Probes	No
Probe Type	2 Air & Load (Silicone Oil)
Ambient Temperature Range	10°C to 32°C
Refrigerant Type	R600a
CFC Free	Yes
HFC Free	Yes
	Yes
HCFC Free	
Ammonia Free	Yes
	Yes No
Ammonia Free UK 3 Pin Plug Other Plug Types Available	No Yes
Ammonia Free UK 3 Pin Plug Other Plug Types Available Voltage Supply	No Yes 220-240V
Ammonia Free UK 3 Pin Plug Other Plug Types Available Voltage Supply Insulation Thickness (mm)	No Yes 220-240V 45mm
Ammonia Free UK 3 Pin Plug Other Plug Types Available Voltage Supply Insulation Thickness (mm) Insulation Type	No Yes 220-240V 45mm High Density Polyurethane Foam
Ammonia Free UK 3 Pin Plug Other Plug Types Available Voltage Supply Insulation Thickness (mm) Insulation Type Blowing Agent	No Yes 220-240V 45mm High Density Polyurethane Foam Cyclopentane
Ammonia Free UK 3 Pin Plug Other Plug Types Available Voltage Supply Insulation Thickness (mm) Insulation Type Blowing Agent Anti Microbial Handle	No Yes  220-240V  45mm  High Density Polyurethane Foam  Cyclopentane Yes
Ammonia Free UK 3 Pin Plug Other Plug Types Available Voltage Supply Insulation Thickness (mm) Insulation Type Blowing Agent Anti Microbial Handle Wall Brackets	No Yes  220-240V  45mm  High Density Polyurethane Foam  Cyclopentane Yes No
Ammonia Free UK 3 Pin Plug Other Plug Types Available Voltage Supply Insulation Thickness (mm) Insulation Type Blowing Agent Anti Microbial Handle Wall Brackets Optional Drawer System	No Yes  220-240V  45mm  High Density Polyurethane Foam  Cyclopentane Yes No No
Ammonia Free UK 3 Pin Plug Other Plug Types Available Voltage Supply Insulation Thickness (mm) Insulation Type Blowing Agent Anti Microbial Handle Wall Brackets	No Yes  220-240V  45mm  High Density Polyurethane Foam  Cyclopentane Yes No





Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

# www.wolflabs.co.uk

Tel: 01759 301142

Fax: 01759 301143

sales@wolflabs.co.uk

Please contact us if this literature doesn't answer all your questions.