



## Dual Probe High Accuracy Data Logger with Graphic

ATMDL-DTP+

- ~ -40 to +125°C (-40 to +257°F) measurement range
- ✓ Stores over 250,000 readings
- ✓ Logging rates between 2 seconds and 1 hour
- On screen menu and graphing to start, stop, review and restart the logger in the field
- ✓ Triggered logging mode to start recording data once a user defined level is met
- ✓ High contrast, greyscale, backlit, graphic LCD screen to denote status and alarm levels
- ✓ User-programmable audible alarm thresholds with highly visible confidence/alarm LEDs

## **SPECIFICATION**

Dimensions	101mm W x 48.5mm H x 30.5mm D
Weight	N/A
Measurement range	-40°C to 125°C
Temperature display on panel	Υ
Accuracy	+/-0.1°C



Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

## www.wolflabs.co.uk

Tel: 01759 301142

Fax: 01759 301143

sales@wolflabs.co.uk

Please contact us if this literature doesn't answer all your questions.