# Miele

### PLW 8683 [LD DC10] Laboratory dishwasher with AD water connection, liquid dispensing & EcoDry function.



- Performance/cycle, e.g. 128laboratory bottles
- Flexible and simple modular load carriers & EasyLoad system
- Maximum user convenience with M Touch Flex full-touch colour display
- Convenient drying support EcoDry
- Connectivity as standard via WiFi
- Efficient use of resources variable speed heater pump

EAN: 4002516883951 / Material number: 12798760 / Old Material Number: 62868338GB

Old Material Number: 62868338GB	
Construction type and version	
Construction type	Freestanding, can be built- under, slimline
Range	ExpertLine
Control panel colour	Black
Casing	Stainless steel
Can be built-under	•
Lid	Stainless Steel
Number of wash levels	2
AutoClose – automatic door lock	•
Buzzer, acoustic signal at end of programme	•
Service-friendly design	•
Application	
Suitable for laboratories	•
Capacity	
Narrow-necked glassware per cycle [number]	64
Test tubes per cycle [number]	196
Vials per cycle [number]	196
Laboratory flasks per cycle [number]	128
Pipettes per cycle [number]	98
Performance data	
Circulation pump, Qmax in I/min	500
Wash cabinet usable capacity in I	145.00
Tested operating hours	15000
Maximum final rinse temperature in °C	93
Control system	
Control type	M Touch Flex
Max. delay start in h	24
Programmability	programmable
Programmes [number]	19
Free programme positions [number]	10
Automatic programme restart	•
Time left display	•
Programme sequence display	•
Selectable display languages	•
Standard electrical connection	
Electrical connection	AC 230V 50HZ
Electric heater rating in kW	5.50
Total rated load in kW	6.30
Fuse rating in A	30-32
Length of mains connection cable in m	1.90
Possible voltage variant 1	
Electrical connection	AC 230V 50HZ
Electric heater rating in kW	2.50
Total rated load in kW	3.30
Fuse rating in A	15-16
Water connection/drainage	10 10
Cold water [number]	1
Osia water [namber]	



EAN: 4002516883951 / Material number: 12798760 /

## PLW 8683 [LD DC10] Laboratory dishwasher with AD water connection, liquid dispensing & EcoDry function.



Old Material Number: 62868338GB	
Hot water [number]	1
Required flow pressure in kPa	200-1000
DI water [number]	1
Maximum delivery head for drain pump in cm	100
Maximum water hardness (cold water/hot water) in mmol/l	10.70
VEP feed pump for demineralised water (option)	•
Drain pump [DN]	22
Integrated water softener	•
Water protection system	Waterproof system
Dimensions and weight	
External dimensions, net height in mm	835
External dimensions, net width in mm	598
External dimensions, net depth in mm	598
Wash cabinet, usable height in mm	520
Wash cabinet, usable width in mm	530
Net weight in kg	74
Dimensions and weight	
External dimensions, gross height in mm	920
External dimensions, gross width in mm	670
External dimensions, gross depth in mm	740
Wash cabinet, depth of upper basket in mm	474
Wash cabinet, depth of lower basket in mm	520
Gross weight in kg	81
Maximum floor load in N/m <sup>2</sup>	1220
Emissions data	
Emissions data Emission sound pressure level in the workplace	<70 dB(A) re 20 μPa
	<70 dB(A) re 20 μPa 5.40
Emission sound pressure level in the workplace	
Emission sound pressure level in the workplace Heat dissipation into the room in MJ/h	
Emission sound pressure level in the workplace Heat dissipation into the room in MJ/h Programmes	
Emission sound pressure level in the workplace Heat dissipation into the room in MJ/h Programmes Standard	
Emission sound pressure level in the workplace Heat dissipation into the room in MJ/h Programmes Standard Intensive	
Emission sound pressure level in the workplace Heat dissipation into the room in MJ/h Programmes Standard Intensive Features	
Emission sound pressure level in the workplace Heat dissipation into the room in MJ/h Programmes Standard Intensive Features Interface for process documentation (optional)	
Emission sound pressure level in the workplace Heat dissipation into the room in MJ/h Programmes Standard Intensive Features Interface for process documentation (optional) Customer Service interface	
Emission sound pressure level in the workplace Heat dissipation into the room in MJ/h Programmes Standard Intensive Features Interface for process documentation (optional) Customer Service interface Extensive components (option)	
Emission sound pressure level in the workplace Heat dissipation into the room in MJ/h Programmes Standard Intensive Features Interface for process documentation (optional) Customer Service interface Extensive components (option) Programmes	
Emission sound pressure level in the workplace Heat dissipation into the room in MJ/h Programmes Standard Intensive Features Interface for process documentation (optional) Customer Service interface Extensive components (option) Programmes Extra short	
Emission sound pressure level in the workplace Heat dissipation into the room in MJ/h Programmes Standard Intensive Features Interface for process documentation (optional) Customer Service interface Extensive components (option) Programmes Extra short Universal	5.40 • • • • • • • • • • • • • • • • • • •
Emission sound pressure level in the workplace Heat dissipation into the room in MJ/h Programmes Standard Intensive Features Interface for process documentation (optional) Customer Service interface Extensive components (option) Programmes Extra short Universal Inorganic	5.40 • • • • • • • • • •
Emission sound pressure level in the workplace Heat dissipation into the room in MJ/h Programmes Standard Intensive Features Interface for process documentation (optional) Customer Service interface Extensive components (option) Programmes Extra short Universal Inorganic Organic	5.40 • • • • • • • • • • • • • • • • • • •
Emission sound pressure level in the workplace Heat dissipation into the room in MJ/h Programmes Standard Intensive Features Interface for process documentation (optional) Customer Service interface Extensive components (option) Programmes Extra short Universal Inorganic Organic Agar	5.40 • • • • • • • • • • • • • • • • •
Emission sound pressure level in the workplace Heat dissipation into the room in MJ/h Programmes Standard Intensive Features Interface for process documentation (optional) Customer Service interface Extensive components (option) Programmes Extra short Universal Inorganic Organic Agar Injector Plus Pipettes Plastics	5.40 • • • • • • • • • • • • • • • • • • •
Emission sound pressure level in the workplace Heat dissipation into the room in MJ/h Programmes Standard Intensive Features Interface for process documentation (optional) Customer Service interface Extensive components (option) Programmes Extra short Universal Inorganic Organic Agar Injector Plus Pipettes Plastics Oil	5.40 • • • • • • • • • • • • • • • • • • •
Emission sound pressure level in the workplace Heat dissipation into the room in MJ/h Programmes Standard Intensive Features Interface for process documentation (optional) Customer Service interface Extensive components (option) Programmes Extra short Universal Inorganic Organic Agar Injector Plus Pipettes Plastics Oil Hygiene 93/10	5.40
Emission sound pressure level in the workplace Heat dissipation into the room in MJ/h Programmes Standard Intensive Features Interface for process documentation (optional) Customer Service interface Extensive components (option) Programmes Extra short Universal Inorganic Organic Agar Injector Plus Pipettes Plastics Oil Hygiene 93/10 Pasteurising	5.40
Emission sound pressure level in the workplace Heat dissipation into the room in MJ/h Programmes Standard Intensive Features Interface for process documentation (optional) Customer Service interface Extensive components (option) Programmes Extra short Universal Inorganic Organic Agar Injector Plus Pipettes Plastics Oil Hygiene 93/10	5.40



Regulation 4 compliant

### PLW 8683 [LD DC10] Laboratory dishwasher with AD water connection, liquid dispensing & EcoDry function.



EAN: 4002516883951 / Material number: 12798760 / Old Material Number: 62868338GB Features 1 dispenser pump for liquid cleaning agent 1 dispenser pump for neutralising agent Suction lance for media canisters 10–20 I (optional) Convenient suction lance DC10 Steam condenser Spray pressure monitoring How-to sequences Chamber lighting Multi-component filter system Variable-speed heater pump Load carrier - direct coupling EcoDry In-door salt container Wash cabinet seamlessly welded using laser technology Heater elements outside wash cabinet EasyLoad Wash cabinet made from high-quality stainless steel (1.4301/304) **Connection options** WiFi Ethernet interface (optional) External dispensing modules Standards, test certificates and symbols IP safety class according to EN 60529: IP 21 EN 61010-2-040 KIWA certificate for water safety Standards, test certificates and symbols EN 61010-1



Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

# www.wolflabs.co.uk

Tel: 01759 301142

Fax: 01759 301143

sales@wolflabs.co.uk

Please contact us if this literature doesn't answer all your questions.