



## Trinocular phase contrast microscope, 1000x, N-PLAN / W-PLAN objectives

<b>Observation Method -</b>	Brightfield	Yes
Transmitted Light	Phase contrast (Positive type)	Yes
	Darkfield	Yes
	Simple polarized light	As optional
Main Body	Туре	Upright
	Construction material	Aluminum die-cast
	Trasportation handle	Yes
Head	Туре	Trinocular (Siedentopf)
	Split ratio	50/50
	Inclination	30°
	360° rotating	Yes
	Interpupillary distance (mm)	48-75
	Diopter adjustment	On both tubes
	Fixing screw for eyepieces	Yes
	Tube inner diameter (mm)	23
Eyepieces	Field number (mm)	20
	Magnification	10x
	Pointer	As optional
	Micrometric scale	As optional
	Diameter of micrometer glass (mm)	21
	High eyepoint (for glass wearers)	Yes
	Rubber cup	Yes
Nosepiece	Positions	Quintuple
	Reversed	Yes
	Bi-directional	Yes
	Rotation on ball bearings	Yes
	Objective thread	RMS

Objectives	Optical system	160
Objectives	Anti-fungus treatment	Yes
	Parfocal distance (mm)	45
	Standard magnifications	43 40x-1000x
	Туре	N-PLAN / W-PLAN
		N-PLAN
		4x/0.10, W.D. 15.2 mm
		W-PLAN PH
		10x/0.25, W.D. 12.2 mm
		W-PLAN PH
		40x/0.65, W.D. 0.37 mm
		W-PLAN PH
		100x/1.25 (Oil),
		W.D. 0.13 mm
•	-	
Stage	Type	Double layer
	Dimensions (mm)	150x139
	Moving mechanism	Rackless
	Moving range (mm)	75x33
	Material	Anti-scratch painting
	Specimen holder	Yes
	Slide number	1
	X-Y Vernier scale	Yes
	Vernier scale accuracy (mm)	0.1
Condenser - Multiple	Туре	Abbe.
Position		Brightfield - Phase contrast - Darkfield (dry)
	Number of positions	5 (BF, 10x/20x, 40x, 100x, DF)
	Numerical aperture (N.A.)	1.25
	Removable	Yes
	Diaphragm	Iris
	Centrable	Yes
	Focusable	By rack and pinion
Focusing System	Туре	Coaxial coarse & fine
	Coarse total travel (mm)	25
	Fine total travel (per single rotation) (mm)	0,2
	Fine graduations	100
	Fine resolution (μm)	2
	Upper stop to prevent contact	Yes
	Adjustable tension	Yes
	Flat knob for ergonomy	Yes
Transmitted	Kohler illumination	Fixed (full as optional)
Illumination	Туре	X-LED
	X-LED type	X-LED3
	Light source power (W)	3.6
	Brightness control	Manual
	Lifetime (hours)	> 65,000
	Temperature (K)	6,300
		0)000
	Max. required power (W)	6

Power Supply for	Туре	External
Transmitted	Microscope connector	Jack, 2.1 mm
Illumination	Power plug type	Multi-plug (EU, UK, US)
	Input voltage	100/240 Vac, 50/60 Hz
	Output voltage	6 Vdc 2.5 A
Accessories Included	Dust cover	Yes
	Immersion oil (10ml)	Yes
	Tension adjustment tool	Yes
	Allen wrench	Yes
	Centering telescope	Yes
	Green filter	Yes
	User Manual	Digital version (downloadable)
Additional Information		External rechargeable battery pack (as optional).
Product Dimensions	Height (mm)	405
	Width (mm)	235
	Depth (mm)	370
Product Weight	(kg)	7,8



Pricing on any accessories shown can be found by keying the part number into the search box on our website. The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

## www.wolflabs.co.uk

Tel : 01759 301142 Fax : 01759 301143 sales@wolflabs.co.uk

Please contact us if this literature doesn't answer all your questions.