



Monocular microscope, 400x, rechargeable, N-PLAN objectives

| Observation Method -<br>Transmitted Light | Brightfield                       | Yes                    |
|---|-----------------------------------|------------------------|
|   | Simple polarized light            | As optional            |
|   |                                   |                        |
| Main Body                                 | Туре                              | Upright                |
|   | Construction material             | Aluminum die-cast      |
|   |                                   |                        |
| Head                                      | Туре                              | Monocular              |
|   | Inclination                       | 30°                    |
|   | 360° rotating                     | Yes                    |
|   | Fixing screw for eyepieces        | Yes                    |
|   | Tube inner diameter (mm)          | 23                     |
|   |                                   |                        |
| Eyepieces                                 | Field number (mm)                 | 18                     |
|   | Magnification                     | 10x                    |
|   | High eyepoint (for glass wearers) | Yes                    |
|   | Pointer                           | As optional            |
|   | Micrometric scale                 | As optional            |
|   | Diameter of micrometer glass (mm) | 20                     |
|   |                                   |                        |
| Nosepiece                                 | Positions                         | Quadruple              |
|   | Bi-directional                    | Yes                    |
|   | Rotation on ball bearings         | Yes                    |
|   | Objective thread                  | RMS                    |
|   |                                   |                        |
| Objectives                                | Optical system                    | 160                    |
|   | Anti-fungus treatment             | Yes                    |
|   | Parfocal distance (mm)            | 45                     |
|   | Standard magnifications           | 40x-400x               |
|   | Туре                              | N-PLAN                 |
|   | Objectives included               | 4x/0.10, W.D. 15.2 mm  |
|   |                                   | 10x/0.25, W.D. 5.5 mm  |
|   |                                   | 40x/0.65, W.D. 0.45 mm |
|   |                                   |                        |
| Stage                                     | Туре                              | Fixed                  |
|   | Dimensions (mm)                   | 130x120                |
|   | Moving mechanism                  | As optional            |
|   | Material                          | Anti-scratch painting  |
|   | Specimen clips                    | Yes                    |
|   | Slide number                      | 1                      |
|   |                                   |                        |
| Condenser - Single Position               | Туре                              | Fixed                  |
|   | Numerical aperture (N.A.)         | 0.65                   |
|   | Diaphragms                        | Iris                   |
|   | Centrable                         | Pre-centered           |

| Focusing System             | Туре   | Coaxial coarse & fine                      |
|-----------------------------|--|--|
|                             | Coarse total travel (mm)                     | 16   |
|                             | Fine total travel (per single rotation) (mm) | 0.4  |
|                             | Fine graduations                             | 100  |
|                             | Fine resolution (µm)                         | 4  |
|                             | Upper stop to prevent contact                | Yes  |
|                             | Adjustable tension                           | Yes  |
|                             |  |  |
| Transmitted<br>Illumination | Туре   | X-LED                                      |
|                             | X-LED type                                   | X-LED1                                     |
|                             | Light source power (W)                       | 1  |
|                             | Brightness control                           | Manual                                     |
|                             | Lifetime (hours)                             | > 65,000                                   |
|                             | Temperature (K)                              | 6,300                                      |
|                             | Max. required power (W)                      | 1.5  |
|                             |  |  |
| Power Supply for            | Туре   | External                                   |
| Transmitted                 | Microscope connector                         | Jack, 2.1 mm                               |
| Illumination                | Power plug type                              | Multi-plug (EU, UK, US)                    |
|                             | Input voltage                                | 100/240 Vac, 50/60 Hz                      |
|                             | Output voltage                               | 5 Vdc 500 mA                               |
|                             | LED indicator                                | Yes  |
|                             | Rechargeable batteries                       | Yes  |
|                             | Battery type                                 | Li-ion (battery pack)                      |
|                             | Working time of batteries (hours)            | 15   |
|                             | Charging time of batteries (hours)           | 6  |
|                             |  |  |
| Accessories Included        | Dust cover                                   | Yes  |
|                             | Tension adjustment tool                      | Yes  |
|                             | User Manual                                  | Digital version (downloadable)             |
|                             |  |  |
| Additional Information      |  | Mirror for transmitted light (as optional) |
| Product Dimensions          | Height (mm)                                  | 350  |
|                             | Width (mm)                                   | 170  |
|                             | Depth (mm)                                   | 320  |
| Product Weight              | (kg)   | 4  |
| , <b>,</b>                  | נפייט  |  |



Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

## www.wolflabs.co.uk

Tel: 01759 301142

Fax: 01759 301143

sales@wolflabs.co.uk

Please contact us if this literature doesn't answer all your questions.